



Certificate Number: 0308991-2

Date: 2017-01-10

UL CONDITIONS OF ACCEPTABILITY

Company Name: TRACO ELECTRONIC AG

File-CCN: E188913-QQGQ2/QQGQ8

Product Description: AC to DC Power Converter

Models: TML 05103, TML 05105, TML 05112, TML 05115, TML 05124, TML 05205, TML 05212, TML 05215, T3029-01A

Conditions Of Acceptability: Conditions of Acceptability - When installed in the end product, consideration shall be given to the following:

1. This component has been judged on the basis of the required spacings in the Standard for Safety of Information Technology Equipment, UL 60950-1, 2nd Edition, 2014-10-14 (Information Technology Equipment - Safety - Part 1: General Requirements) and CSA C22.2 No. 60950-1-07, 2nd Edition, 2014-10 (Information Technology Equipment - Safety - Part 1: General Requirements), Sub-clause 2.10, which would cover the component itself if submitted for Listing.
2. The products were tested on a 20 A branch circuit. If used on a branch circuit greater than this, additional testing may be necessary.
3. Base rated minimum 94HB and is considered a decorative part.
4. All secondary output circuits are SELV and are not hazardous energy levels.
5. The secondary output circuits do not exceed 240 VA at a potential of 2 V or more.
6. The terminals and connectors have not been evaluated for field wiring.
7. The equipment has been evaluated for use in a Pollution Degree 1 and 2 environment, since the power converter is potted.
8. The grounding shall be evaluated in the end product.

Ratings:

Model	Voltage/Current	Voltage/Current
TML05103	+3.3 V/1.5 A	---
TML 05105	+5 V/1 A	---
TML 05112	+12 V/0.416 A	---
TML 05115	+15 V/0.333 A	---
TML 05124	+24 V/0.2 A	---
TML 05205	+5 V/0.5 A	-5 V/0.5 A
TML 05212	+12 V/0.2 A	-12 V/0.2 A
TML 05215	+15 V/0.16 A	-15 V/0.16 A
T3029-01A	+5 V/1 A	---

This document is for reference only. It is current as of the date referenced above, and is subject to change at any time without notice.