

CE TEST REPORT

of
EN 55032 / CISPR 32 / AS/NZS CISPR 32
Class A
EN 55024 / CISPR 24 / IMMUNITY

Product : **THN 10 Series**

Model(s): **THN 10-2415WIRzzzzzz**

(more serial models listed on 1.3 of this test report)



Brand: **TRACO POWER**

Applicant: **TRACO ELECTRONIC AG**

Address: **Sihlbruggstrasse 111 CH-6340
Baar Switzerland**

Test Performed by:

International Standards Laboratory Corp.

<LT LAB>

*Address:

No. 120, Lane 180, Hsin Ho Rd.,
Lung-Tan Dist., Tao Yuan City 325, Taiwan
*Tel: 886-3-407-1718; Fax: 886-3-407-1738

Report No.: **ISL-19LE557CE-1-MA**

Issue Date : **December 6, 2019**

This report totally contains 63 pages including this cover page and contents page.

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

Contents of Report

1.	General	1
1.1	Certification of Accuracy of Test Data.....	1
1.2	Test Standards.....	2
1.3	Model Number Definition	5
1.4	Description of EUT	6
1.5	Description of Support Equipment	9
2.	Power Main Port Conducted Emissions	10
2.1	Test Setup and Procedure	10
2.2	Conduction Test Data: Configuration 1.....	12
2.3	Test Setup Photo.....	14
3.	Telecommunication Port Conducted Emissions	16
3.1	Test Setup and Procedure	16
4.	Radiated Disturbance Emissions.....	18
4.1	Test Setup and Procedure	18
4.2	Limit	20
4.3	Radiation Test Data: Configuration 1.....	22
4.4	Test Setup Photo.....	26
5.	Voltage Disturbance Emissions at Antenna Terminals	28
5.1	Test Setup and Procedure	28
6.	Differential Voltage Emissions.....	30
6.1	Test Setup and Procedure	30
7.	Outdoor units of home satellite receiving systems	32
7.1	Test Setup and Procedure	32
8.	Electrostatic discharge (ESD) immunity	34
8.1	Test Specification and Setup	34
8.2	Test Data: Configuration 1	35
8.3	Test Point.....	36
8.4	Test Setup Photo.....	37
9.	Radio-Frequency, Electromagnetic Field immunity.....	38
9.1	Test Specification and Setup	38
9.2	Test Data: Configuration 1	39
9.3	Test Setup Photo.....	40
10.	Electrical Fast transients/burst immunity.....	41
10.1	Test Specification and Setup	41
10.2	Test Data: Configuration 1	43
10.3	Test Setup Photo.....	45
11.	Surge Immunity	46
11.1	Test Specification and Setup	46
11.2	Test Data: Configuration 1	47
11.3	Test Setup Photo.....	48
12.	Immunity to Conductive Disturbance.....	49
12.1	Test Specification and Setup	49
12.2	Test Data: Configuration 1	50
12.3	Test Setup Photo.....	51
13.	Power Frequency Magnetic Field immunity.....	52
13.1	Test Specification and Setup	52
13.2	Test Data: Configuration 1	53
13.3	Test Setup Photo.....	54

14. Appendix.....	55
14.1 Appendix A: Test Equipment.....	55
14.2 Appendix B: Uncertainty of Measurement	58
14.3 Appendix C: Photographs of EUT Please refer to the File of ISL-19LE557P-1-MA.	60

1. General

1.1 Certification of Accuracy of Test Data

Standards: Please refer to 1.2

Equipment Tested: THN 10 Series

Model: THN 10-2415WIRzzzzzz
(more serial models listed on 1.3 of this test report)



Brand: TRACO POWER

Applicant: TRACO ELECTRONIC AG

Sample received Date: August 31, 2019

Final test Date: EMI: refer to the date of test data

EMS: September 18, 2019

Test Site: Chamber 02; Chamber 14; Conduction 03; Immunity 02

Test Distance: 10M; 3M (above 1GHz) (EMI test)

Temperature: refer to each site test data

Humidity: refer to each site test data

Atmospheric Pressure: 86 kPa to 106 kPa

Input power: Conduction input power: DC 24 V

Radiation input power: DC 24 V

Immunity input power: DC 24 V

Test Result: PASS

Report Engineer: Cheryl Tung

Test Engineer:

Hasan Yu
Hasan Yu

Approved By:

Benson Chen

Benson Chen / Associate Director

1.2 Test Standards

The tests which this report describes were conducted by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp. in accordance with the following

EN 55032:2015+AC:2016, CISPR 32: 2015+COR1:2016: Class A: Electromagnetic compatibility of multimedia equipment - Emission requirements.

AS/NZS CISPR 32:2015: Class A: Electromagnetic compatibility of multimedia equipment- Emission requirements

Performed Item	Test Performed	Deviation	Result
Conducted emissions from the DC mains power ports	Yes	No	PASS
Telecommunication Port Conducted Emissions (asymmetric mode)	N/A	N/A	N/A
Radiated emissions at frequencies below 1 GHz	Yes	No	PASS
Radiated emissions at frequencies above 1 GHz	Yes	No	PASS
Radiated emissions from FM receivers	N/A	N/A	N/A
Voltage Disturbance Emissions at Antenna Terminals	N/A	N/A	N/A
Differential voltage emissions	N/A	N/A	N/A
Outdoor units of home satellite receiving systems	N/A	N/A	N/A

EN 55024:2010+A1:2015 and CISPR 24:2010+A1:2015: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4:2012 IEC 61000-4-4:2012	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5:2014+A1:2017 IEC 61000-4-5:2014+A1:2017	Surge	Pass	B
EN 61000-4-6:2014+AC:2015 IEC 61000-4-6:2013	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11:2004+A1:2017 IEC 61000-4-11:2004+A1:2017	Voltage Dips / Short Interruption and Voltage Variation		
	>95% in 0.5 period	N/A	B
	30% in 25 period	N/A	C
	>95% in 250 period	N/A	C

Standard	Description	Results
EN 61000-3-2:2014 IEC 61000-3-2:2014	Limits for harmonics current emissions	N/A
EN 61000-3-3:2013 IEC 61000-3-3:2013	Limits for voltage fluctuations and flicker in low-voltage supply systems.	N/A

1.2.1 Performance Criteria for Compliance: EN 55024

Performance criterion A

During and after the test the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a minimum performance level specified by the manufacturer when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion B

After the test, the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion C

During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.

Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

1.3 Model Number Definition

There are more than one model number for this product, please refer the details listed below:

THN 10-2410WIRzzzzzz; THN 10-2411WIRzzzzzz; THN 10-2412WIRzzzzzz; THN

10-2413WIRzzzzzz; THN 10-2415WIRzzzzzz; THN 10-2421WIRzzzzzz; THN

10-2422WIRzzzzzz; THN 10-2423WIRzzzzzz; THN 10-2425WIRzzzzzz; THN

10-4810WIRzzzzzz; THN 10-4811WIRzzzzzz; THN 10-4812WIRzzzzzz; THN

10-4813WIRzzzzzz; THN 10-4815WIRzzzzzz; THN 10-4821WIRzzzzzz; THN

10-4822WIRzzzzzz; THN 10-4823WIRzzzzzz; THN 10-4825WIRzzzzzz; THN

10-7210WIRzzzzzz; THN 10-7211WIRzzzzzz; THN 10-7212WIRzzzzzz; THN

10-7213WIRzzzzzz; THN 10-7215WIRzzzzzz; THN 10-7221WIRzzzzzz; THN

10-7222WIRzzzzzz; THN 10-7223WIRzzzzzz; THN 10-7225WIRzzzzzz;

z can be any alphanumeric or dash or blank

1.4 Description of EUT

EUT

This report test data using the report number 19LE557CE-1

Description	THN 10 Series
Condition	Pre-Production
Model	THN 10-2415WIRzzzzzz (more serial models listed on 1.3 of this test report)
Serial Number	N/A
Highest working frequency:	395kHz

Test configuration:

Configuration	Model Name	Input VDC	Output Voltage VDC	Output Current mA
1	THN 10-2415WIRzzzzzz	24	24	420

For EMS (Not Include Electrical Fast transients/burst immunity & Surge Immunity) test

Configuration	Model Name	Input VDC	Output Voltage VDC	Output Current mA	With an aluminum electrolytic capacitor test board
1	THN 10-2415WIRzzzzzz	24	24	420	No

For Electrical Fast transients/burst immunity & Surge Immunity test mode

Configuration	Model Name	Input VDC	Output Voltage VDC	Output Current mA	With an aluminum electrolytic capacitor test board
1	THN 10-2415WIRzzzzzz	24	24	420	Yes

Different Model list:

Model Name	Input Range (VDC)	Output Voltage (VDC)	Output Current@Full Load (mA)
THN 10-2410WIRzzzzzz	9 ~ 36	3.3	3000
THN 10-2411WIRzzzzzz	9 ~ 36	5	2000
THN 10-2412WIRzzzzzz	9 ~ 36	12	830
THN 10-2413WIRzzzzzz	9 ~ 36	15	670
THN 10-2415WIRzzzzzz	9 ~ 36	24	420
THN 10-2421WIRzzzzzz	9 ~ 36	±5	±1000
THN 10-2422WIRzzzzzz	9 ~ 36	±12	±416
THN 10-2423WIRzzzzzz	9 ~ 36	±15	±333
THN 10-2425WIRzzzzzz	9 ~ 36	±24	±210
THN 10-4810WIRzzzzzz	18 ~ 75	3.3	3000
THN 10-4811WIRzzzzzz	18 ~ 75	5	2000
THN 10-4812WIRzzzzzz	18 ~ 75	12	830
THN 10-4813WIRzzzzzz	18 ~ 75	15	670
THN 10-4815WIRzzzzzz	18 ~ 75	24	420
THN 10-4821WIRzzzzzz	18 ~ 75	±5	±1000
THN 10-4822WIRzzzzzz	18 ~ 75	±12	±416
THN 10-4823WIRzzzzzz	18 ~ 75	±15	±333
THN 10-4825WIRzzzzzz	18 ~ 75	±24	±210

Model Name	Input Range (VDC)	Output Voltage (VDC)	Output Current@Full Load (mA)
THN 10-7210WIRzzzzzz	36 ~ 160	3.3	3000
THN 10-7211WIRzzzzzz	36 ~ 160	5	2000
THN 10-7212WIRzzzzzz	36 ~ 160	12	830
THN 10-7213WIRzzzzzz	36 ~ 160	15	670
THN 10-7215WIRzzzzzz	36 ~ 160	24	420
THN 10-7221WIRzzzzzz	36 ~ 160	±5	±1000
THN 10-7222WIRzzzzzz	36 ~ 160	±12	±416
THN 10-7223WIRzzzzzz	36 ~ 160	±15	±333
THN 10-7225WIRzzzzzz	36 ~ 160	±24	±210
z can be any alphanumeric or dash or blank			

EMI Noise Source:

Please refer to the technical documents.

EMI Solution:

Please refer to the technical documents.


1.5 Description of Support Equipment

No	Unit	Model Serial No.	Brand	Power Cord	FCC ID
1	DC Power Source	GPD-4050D S/N: N/A	GW INSTEK	Non-shielded	FCC DOC
2	Dummy Load	N/A S/N: N/A	N/A	N/A	N/A

2. Power Main Port Conducted Emissions

2.1 Test Setup and Procedure

2.1.1 Test Setup



2.1.2 Test Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, live and neutral, were measured. All of the interface cables were manipulated according to EN 55032 requirements.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

2.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150kHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9kHz

2.1.4 Limit

Conducted emissions from the DC mains power ports of Class A equipment:

Frequency	QP	AV
MHz	dB(μV)	dB(μV)
0.15-0.50	79	66
0.50-30	73	60

Note: The lower limit shall apply at the transition frequencies

Conducted emissions from the DC mains power ports of Class B equipment:


Frequency	QP	AV
MHz	dB(μV)	dB(μV)
0.15-0.50	66-56	56-46
0.50-5.0	56	46
5.0-30	60	50

Note: The lower limit shall apply at the transition frequencies

Customers require testing for DC products, non-regulatory requirements.

2.2 Conduction Test Data: Configuration 1

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.354	49.26	49.53	10.14	59.40	79.00	-19.60	59.67	66.00	-6.33
2	0.710	44.79	45.01	10.17	54.96	73.00	-18.04	55.18	60.00	-4.82
3	1.062	40.45	40.73	10.17	50.62	73.00	-22.38	50.90	60.00	-9.10
4	1.770	41.46	41.70	10.21	51.67	73.00	-21.33	51.91	60.00	-8.09
5	2.830	39.93	40.20	10.27	50.20	73.00	-22.80	50.47	60.00	-9.53
6	3.890	40.57	40.65	10.31	50.88	73.00	-22.12	50.96	60.00	-9.04

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor


Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.354	49.86	50.13	10.14	60.00	79.00	-19.00	60.27	66.00	-5.73
2	0.706	45.46	45.72	10.17	55.63	73.00	-17.37	55.89	60.00	-4.11
3	1.062	42.55	42.83	10.18	52.73	73.00	-20.27	53.01	60.00	-6.99
4	1.414	43.04	43.30	10.20	53.24	73.00	-19.76	53.50	60.00	-6.50
5	3.890	42.42	42.55	10.31	52.73	73.00	-20.27	52.86	60.00	-7.14
6	4.246	42.47	42.61	10.32	52.79	73.00	-20.21	52.93	60.00	-7.07
7	4.954	42.91	42.84	10.35	53.26	73.00	-19.74	53.19	60.00	-6.81
8	6.014	42.51	42.73	10.39	52.90	73.00	-20.10	53.12	60.00	-6.88

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit



The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.
 If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.3 Test Setup Photo

Front View




Back View



3. Telecommunication Port Conducted Emissions

3.1 Test Setup and Procedure

3.1.1 Test Setup



3.1.2 Test Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

The EUT, any support equipment, and any interconnecting cables were arranged and moved to get the maximum measurement. All of the interface cables were manipulated according to EN 55032 requirements.

The port of the EUT was connected to the support equipment through the ISN and linked in normal condition.

DC input power for the EUT & the support equipment power outlets were obtained from the same filtered source that provided input power to the LISN.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information could be useful in reducing their amplitude.

3.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150kHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9kHz

3.1.4 Limit

Asymmetric mode conducted emissions from Class_A equipment:

Applicable to

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. antenna ports.

Frequency range MHz	Coupling device	Detector type / bandwidth	Class_A voltage limits dB(μV)	Class_A current limits dB(μA)	
0.15-0.5	AAN	Quasi Peak / 9 kHz	97-87	n/a	
0.5-30			87		
0.15-0.5	AAN	Average / 9 kHz	84-74	n/a	
0.5-30			74		
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	97-87	53-43	
0.5-30			87	43	
0.15-0.5	CVP and current probe	Average / 9 kHz	84-74	40-30	
0.5-30			74	30	
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	53-43	
0.5-30				43	
0.15-0.5	Current Probe	Average / 9 kHz		40-30	
0.5-30				30	

Asymmetric mode conducted emissions from Class_B equipment:

Applicable to:

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. broadcast receiver tuner ports.
4. antenna ports.




Frequency range MHz	Coupling device	Detector type / bandwidth	Class_B voltage limits dB(μV)	Class_B current limits dB(μA)	
0.15-0.5	AAN	Quasi Peak / 9 kHz	84-74	n/a	
0.5-30			74		
0.15-0.5	AAN	Average / 9 kHz	74-64	n/a	
0.5-30			64		
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	84-74	40-30	
0.5-30			74	30	
0.15-0.5	CVP and current probe	Average / 9 kHz	74-64	30-20	
0.5-30			64	20	
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	40-30	
0.5-30				30	
0.15-0.5	Current Probe	Average / 9 kHz		30-20	
0.5-30				20	

****Remarks: It is not necessary to be tested on this item.**

4. Radiated Disturbance Emissions

4.1 Test Setup and Procedure

4.1.1 Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.

Frequency (GHz)	E-plane	H-plane	$\theta_{3\text{dB}}(\text{min})$	d= 3 m
				w (m)
1	88°	147°	88°	5.79
2	68°	119°	68°	4.04
3	73°	92°	73°	4.44
4	70°	89°	70°	4.20
5	55°	60°	55°	3.12
6	63°	62°	62°	3.60

4.1.2 Test Procedure

The radiated emissions test will then be repeated on the open site or chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter open field sites or 10 meter chamber. Desktop EUT are set up on a FRP stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 6 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to EN 55032 requirements.

The highest internal source of an EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes.

If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz.

If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.

If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.

If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.

4.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 30MHz--1000MHz
 Detector Function: Quasi-Peak Mode
 Resolution Bandwidth: 120kHz

Frequency Range: Above 1 GHz to 6 GHz
 Detector Function: Peak/Average Mode
 Resolution Bandwidth: 1MHz

4.2 Limit

Radiated emissions at frequencies up to 1 GHz for Class A equipment:

Frequency range MHz	Measurement		Class_A limits dB(µV/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	40
230-1000			47
30-230			50
230-1000			57

Radiated emissions at frequencies above 1 GHz for Class A equipment:

Frequency range MHz	Measurement		Class_A limits dB(µV/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	56
3000-6000			60
1000-3000		Peak / 1MHz	76
3000-6000			80

Radiated emissions at frequencies up to 1 GHz for Class B equipment:

Frequency range MHz	Measurement		Class_B limits dB(µV/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	30
230-1000			37
30-230			40
230-1000			47

Radiated emissions at frequencies above 1 GHz for Class_B equipment:


Frequency range MHz	Measurement		Class_B limits dB(μV/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	50
3000-6000		Peak / 1MHz	54
1000-3000		Peak / 1MHz	70
3000-6000		Peak / 1MHz	74

Radiated emissions from FM receivers:

Frequency range MHz	Measurement		Class_B limits dB(μV/m)	
	Distance m	Detector type / bandwidth	Fundamental	Harmonics
			OATS/SAC	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	50	42
230-300				42
300-1000			60	46
30-230	3	Quasi Peak / 120 kHz	52	52
230-300				52
300-1000			60	56

4.3 Radiation Test Data: Configuration 1

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	399.57	47.14	-12.14	35.00	47.00	-12.00	200	33	peak
2	549.92	41.89	-9.33	32.56	47.00	-14.44	300	295	peak
3	575.14	42.74	-8.59	34.15	47.00	-12.85	400	300	peak
4	600.36	45.28	-7.73	37.55	47.00	-9.45	400	163	peak
5	825.40	33.89	-4.17	29.72	47.00	-17.28	300	258	peak
6	941.80	31.80	-2.49	29.31	47.00	-17.69	200	359	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan.
 Tel: 03-4071718



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1200.00	60.07	-15.62	44.45	76.00	-31.55	229	0	peak
2	1275.00	58.06	-15.36	42.70	76.00	-33.30	200	344	peak
3	1400.00	59.67	-15.78	43.89	76.00	-32.11	200	332	peak
4	1525.00	60.59	-16.25	44.34	76.00	-31.66	200	326	peak
5	1575.00	61.05	-16.02	45.03	76.00	-30.97	200	342	peak
6	1650.00	58.68	-15.14	43.54	76.00	-32.46	146	360	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor


Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

-Radiated Emissions (Vertical)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	53.28	45.57	-17.00	28.57	40.00	-11.43	100	317	peak
2	136.70	47.67	-17.06	30.61	40.00	-9.39	100	78	peak
3	400.54	47.52	-12.12	35.40	47.00	-11.60	400	130	peak
4	524.70	44.81	-9.58	35.23	47.00	-11.77	100	27	peak
5	575.14	45.09	-8.59	36.50	47.00	-10.50	100	267	peak
6	600.36	46.25	-7.73	38.52	47.00	-8.48	100	13	peak
7	800.18	38.61	-4.48	34.13	47.00	-12.87	100	109	peak
8	906.88	43.87	-3.05	40.82	47.00	-6.18	100	60	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit


Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan.
 Tel: 03-4071718

Radiated Emission Measurement
 Date: 2019/9/4 Operator: Juanwei
 Temperature: 26 °C Humidity: 60 %



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1200.00	59.25	-15.62	43.63	76.00	-32.37	100	318	peak
2	1600.00	57.82	-15.86	41.96	76.00	-34.04	193	360	peak
3	2465.00	55.16	-11.76	43.40	76.00	-32.60	181	360	peak
4	2600.00	53.81	-11.38	42.43	76.00	-33.57	139	360	peak
5	2950.00	53.00	-11.15	41.85	76.00	-34.15	176	360	peak
6	3000.00	52.26	-11.04	41.22	76.00	-34.78	200	317	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters


Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

4.4 Test Setup Photo


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)




Back View (above 1GHz)



5. Voltage Disturbance Emissions at Antenna Terminals

5.1 Test Setup and Procedure

5.1.1 Test Setup



5.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dBuV at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

5.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

5.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.

Table clause	Frequency range MHz	Detector type/bandwidth	Class B limits dB(μ V) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies \leq 1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300	For frequencies \geq 1 GHz	46	54	50	See c)
	300 – 1 000				52	
A12.4	30 – 300	Peak/ 1 MHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	


a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.
 b) Tuner units (not the LNB) for satellite signal reception.
 c) Frequency modulation audio receivers and PC tuner cards.
 d) Frequency modulation car radios.
 e) Applicable to EUs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.

****Remarks: It is not necessary to be tested on this item.**

6. Differential Voltage Emissions

6.1 Test Setup and Procedure

6.1.1 Test Setup



6.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dB_{UV} at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

6.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

6.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.

Table clause	Frequency range MHz	Detector type/bandwidth	Class B limits dB(μ V) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies \leq 1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300	For frequencies \geq 1 GHz	46	54	50	See c)
	300 – 1 000				52	
A12.4	30 – 300	Peak/ 1 MHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	


a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.
 b) Tuner units (not the LNB) for satellite signal reception.
 c) Frequency modulation audio receivers and PC tuner cards.
 d) Frequency modulation car radios.
 e) Applicable to EUs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.

****Remarks: It is not necessary to be tested on this item.**

7. Outdoor units of home satellite receiving systems

7.1 Test Setup and Procedure

7.1.1 Test Setup



7.1.2 Test Procedure

The input signal shall be adjusted to get the maximum rated output level from the EUT. For the measurement in the frequency range from 30 MHz to 18 GHz the input signal shall be adjusted so that the output frequency is within this frequency range. For the measurement in the frequency range above 1 GHz, the frequency of the input signal shall be adjusted in such a way that the EUT is measured, as a minimum, at the lowest, middle and highest rated output frequency within the measured frequency range.

7.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	30MHz--1000MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz
Frequency Range:	Above 1000MHz
Detector Function:	Peak/Average Mode
Resolution Bandwidth:	1MHz

7.1.4 Limit

Table Clause	Frequency Range MHz	Measurement			Class B Limits	Applicable to
		Facility (see Table A.1)	Distance m	Detector type / Bandwidth		
A7.1	30 to 1 000	SAC / OATS / FAR	See Table A.4	Quasi Peak / 120 kHz	See Table A.4	
A7.2	1 000 to 2 500	FSOATS	3	Average / 1 MHz	50 dB(μ V/m)	LO leakage and spurious radiated emissions from the EUT, in the region outside $\pm 7^\circ$ of the main beam axis. See Figure H.1
	2 500 to 18 000				64 dB(μ V/m)	
A7.3	1 000 to 18 000	FSOATS	3	Average / 1 MHz	37 dB(μ V/m)	LO leakage from the EUT, in the region within $\pm 7^\circ$ of the main beam axis. See Figure H.1
A7.4	1 000 to 18 000	Conducted (Clause H.4)	n/a	Average / 1 MHz	30 dBpW	

For details of the EUT configuration, see Annex H.

For radiated emissions measurements at frequencies up to 1 GHz, the requirements defined in Table A.4 shall be satisfied.

Apply the appropriate limits across the entire frequency range.

Apply the limits defined in table Clause A7.1 and A7.2. Also apply the limits defined in either table Clause A7.3 or A7.4.

****Remarks: It is not necessary to be tested on this item.**

8. Electrostatic discharge (ESD) immunity

8.1 Test Specification and Setup

8.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-2/ IEC 61000-4-2 (details referred to Sec 1.2)
Test Level:	Air +/- 2 kV, +/- 4 kV, +/- 8 kV Contact +/- 4 kV, +/- 6 kV
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S7

Selected Test Point


Air: discharges were applied to slots, aperture or insulating surfaces. 10 single air discharges were applied to each selected points.

Contact: Total 200 discharges minimum were to the selected contact points.

Indirect Contact Points: 25 discharges were applied to center of one edge of VCP and each EUT side of HCP with 10 cm away from EUT.

8.1.2 Test Setup

EUT is 1m from the wall and other metallic structure. When Battery test mode is needed, a cable with one 470KΩ resistor at two rare ends is connected from metallic part of EUT and screwed to HCP.



8.1.3 Test Result

Performance of EUT complies with the given specification

8.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-2	Date
EUT Model Name	THN 10-2415WIRzzzzzz	2019-09-10
Barometer Pressure		Engineer
Temperature	25°C	SAWYER
Humidity	56%	EM TEST(Model: Dito)
Voltage/Freq.	24 Vdc	

A=criteria A, B=criteria B, C=criteria C

→ Blue arrow represent Air discharge point

→ Red arrow represent Contact discharge point

ND=No Discharge (No Arcing); Meets criteria but unable to obtain an electrostatic discharge (ESD) at this test point.

X=EUT DOES NOT meet the acceptance criteria

A=criteria A, B=criteria B, C=criteria C

Contact Discharge	Voltage kV 25 Discharge @ 1 PPS								Comments
Test Location	+4	-4	+6	-6					
1	ND	ND	ND	ND					
2	ND	ND	ND	ND					
3	ND	ND	ND	ND					
4	ND	ND	ND	ND					
5	ND	ND	ND	ND					
Air Discharge	Voltage kV 10 Discharge @ 1 PPS								Comments
Test Location	+2	-2	+4	-4	+8	-8			
1	ND	ND	ND	ND	A	A			
2	ND	ND	ND	ND	A	A			
3	ND	ND	ND	ND	A	A			
4	ND	ND	ND	ND	A	A			
5	ND	ND	ND	ND	A	A			
Indirect Discharge	Voltage kV 25 Discharge @ 1 PPS								Comments
Test Location	+4	-4	+6	-6					
VCP Front	A	A	A	A					
VCP Right	A	A	A	A					
VCP Left	A	A	A	A					
VCP Back	A	A	A	A					
Test Location	+4	-4	+6	-6					Comments
HCP Front	A	A	A	A					
HCP Right	A	A	A	A					
HCP Left	A	A	A	A					
HCP Back	A	A	A	A					

Additional Notes: A=criteria A, B=criteria B, C=criteria C

8.3 Test Point

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.

Figure 1 : Test Point Assignments Discharge:






Figure 2 : Test Point Assignments Discharge:



8.4 Test Setup Photo



9. Radio-Frequency, Electromagnetic Field immunity


9.1 Test Specification and Setup

9.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-3/ IEC 61000-4-3 (details referred to Sec 1.2)
Test Level:	10 V/m
Modulation:	AM 1kHz 80%
Frequency range:	80 MHz~1 GHz
Frequency Step:	1% of last step frequency
Dwell time:	3s
Polarization:	Vertical and Horizontal
EUT Azimuth Angle	<input checked="" type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input checked="" type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S8

9.1.2 Test Setup

The field sensor is placed at one calibration grid point to check the intensity of the established fields on both polarizations. EUT is adjusted to have each side of EUT face coincident with the calibration plane. A CCD camera and speakers are used to monitor the condition of EUT for the performance judgment.



9.1.3 Test Result

Performance of EUT complies with the given specification

9.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-3	Date
EUT Model Name	THN 10-2415WIRzzzzzz	2019-09-18
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	Chamber 04
Voltage/Freq.	24 Vdc	

A=criteria A, B=(criteria B, C=Criteria C

EUT Angle	Frequency		Dwell time	Modulation	Level (V/m)	Antenna Polarization	EUT Status	Comments
	Range (MHz)	Steps %						
0°(front)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
90°(left)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
180°(back)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
270°(right)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
0°(front)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	
90°(left)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	
180°(back)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	
270°(right)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	

Additional Notes: A=Criteria A, B=Criteria B, C=Criteria C

9.3 Test Setup Photo



10. Electrical Fast transients/burst immunity

10.1 Test Specification and Setup

10.1.1 Test Specification

Port:	DC mains
Basic Standard:	EN 61000-4-4/ IEC 61000-4-4 (details referred to Sec 1.2)
Test Level:	DC Power Port: +/- 2 kV
Rise Time:	5ns
Hold Time:	50ns
Burst Period:	300ms
Repetition Frequency:	5kHz
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S9

Test Procedure


The EUT was setup on a nonconductive table 0.1 m above a reference ground plane.

Test Points	Polarity	Result	Comment
Line	+	N	60 sec
	-	N	60 sec
Neutral	+	N	60 sec
	-	N	60 sec
Line to Neutral	+	N	60 sec
	-	N	60 sec

Note: 'N' means normal, the EUT function is correct during the test.

10.1.2 Test Setup

EUT is at least 50cm from the conductive structure.



10.1.3 Test Result

Performance of EUT complies with the given specification

10.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-4	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-10
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	EM TEST (Model: UCS-500 M6B)
Voltage/Freq.	24 Vdc	

A=criteria A, B=criteria B, C=criteria C

 AC Power Port: DC Power Port: LAN Port: Telephone Port:
DC Power Port

Line Under Test	Voltage Level	Severity Level	Pulse Polarity	Burst Repetition Rate	Test Duration	EUT Status	Comments
Line	0.5kV	1	+	300ms / 5.0kHz	1 Minutes	A	
Line	0.5kV	1	-	300ms / 5.0kHz	1 Minutes	A	
Neutral	0.5kV	1	+	300ms / 5.0kHz	1 Minutes	A	
Neutral	0.5kV	1	-	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	0.5kV	1	+	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	0.5kV	1	-	300ms / 5.0kHz	1 Minutes	A	
Line	1.0kV	2	+	300ms / 5.0kHz	1 Minutes	A	
Line	1.0kV	2	-	300ms / 5.0kHz	1 Minutes	A	
Neutral	1.0kV	2	+	300ms / 5.0kHz	1 Minutes	A	
Neutral	1.0kV	2	-	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	1.0kV	2	+	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	1.0kV	2	-	300ms / 5.0kHz	1 Minutes	A	
Line	2.0kV	3	+	300ms / 5.0kHz	1 Minutes	A	
Line	2.0kV	3	-	300ms / 5.0kHz	1 Minutes	A	
Neutral	2.0kV	3	+	300ms / 5.0kHz	1 Minutes	A	
Neutral	2.0kV	3	-	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	2.0kV	3	+	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	2.0kV	3	-	300ms / 5.0kHz	1 Minutes	A	

Additional Notes: A=criteria A, B=criteria B, C=criteria C

NOTE:

With an aluminum electrolytic capacitor (Nippon chemi-con KY series, 470μF/50V) and a TVS (SMDJ58A, 58V, 3000Watt peak pulse power) in parallel.



10.3 Test Setup Photo




11. Surge Immunity

11.1 Test Specification and Setup

11.1.1 Test Specification

Port:	DC mains
Basic Standard:	EN 61000-4-5/ IEC 61000-4-5 (details referred to Sec 1.2)
Test Level:	Line to Line: +/- 0.5 kV, +/- 1 kV, +/- 2kV
Rise Time:	1.2us
Hold Time:	50us
Repetition Rate:	30 seconds
Angle:	<input checked="" type="checkbox"/> 0° <input type="checkbox"/> 90° <input checked="" type="checkbox"/> 180° <input type="checkbox"/> 270°
Criteria:	B
Remarks:	
Test Procedure:	`refer to ISL QA -T4-E-S10

11.1.2 Test Setup



11.1.3 Test Result

Performance of EUT complies with the given specification


11.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-5	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-10
Barometer Pressure	102.2kPa	Engineer
Temperature	25°C	SAWYER
Humidity	56%	Equipment & Test Site
Voltage/Freq.	24 Vdc	EMC PARTNER (Model:MIG0603IN3)

A=criteria A, **B=**criteria B, **C=**criteria C

AC Power Port: DC Power Port: LAN Port: Telephone Port:

DC Power Port

Line Under Test	Voltage	Level	Polarity	Repetition Rate	Cycle	Pulse Position	EUT Status	Comments
Line-Neutral	0.5kV	2	+	30 sec	5		A	
Line-Neutral	0.5kV	2	-	30 sec	5		A	
Line- Neutral	1.0kV	2	+	30 sec	5		A	
Line- Neutral	1.0kV	2	-	30 sec	5		A	
Line- Neutral	2.0kV	3	+	30 sec	5		A	
Line- Neutral	2.0kV	3	-	30 sec	5		A	

Additional Notes: A=criteria A, B=criteria B, C=criteria C

NOTE:

With an aluminum electrolytic capacitor (Nippon chemi-con KY series, 470μF/50V) and a TVS (SMDJ58A, 58V, 3000Watt peak pulse power) in parallel.



11.3 Test Setup Photo




12. Immunity to Conductive Disturbance

12.1 Test Specification and Setup

12.1.1 Test Specification

Port:	DC mains
Basic Standard: (By manufacture reference)	EN 61000-4-6/ IEC 61000-4-6 (details referred to Sec 1.2)
Test Level:	10 V
Modulation:	AM 1kHz 80%
Frequency range:	0.15 MHz - 80MHz
Frequency Step:	1% of last Frequency
Dwell time:	3s
Criteria:	A
CDN Type:	CDN M2+M3
Test Procedure	refer to ISL QA -T4-E-S11

12.1.2 Test Setup



12.1.3 Test Result

Performance of EUT complies with the given specification

12.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-6	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-06
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	FRANKONIA (Model: CIT-10/75)
Voltage/Freq.	24 Vdc	

A=criteria A, **B=**criteria B, **C=**criteria C

DC Power Port

Line Under Test	Frequency		Level	Modulation	Dwell time	EUT Status	Comments
	Range (MHz)	Steps %					
DC Power Port	0.15 to 80	1	10V	80% @ 1kHz	3s	A	
Additional Notes: A=criteria A, B=criteria B, C=criteria C							

12.3 Test Setup Photo




13. Power Frequency Magnetic Field immunity

13.1 Test Specification and Setup

13.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-8/ IEC 61000-4-8 (details referred to Sec 1.2)
Test Level:(By manufacture reference)	100A/m , continuous
Test Level:(By manufacture reference)	1000A/m , 1 sec
Polarization:	X, Y, Z
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S12

13.1.2 Test Setup



13.1.3 Test Result

Performance of EUT complies with the given specification

13.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-8	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-06
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	FCC(F-1000-4-8-G-125A) Immunity Loop: FCC (F-100-4-8-L-1M)
Voltage/Freq.	24 Vdc	

A=criteria A, B=criteria B, C=criteria C

Antenna Polarization	Frequency (Hz)	Test Level	Test Duration	EUT Status	Comment
X	50	100 A/m	1 Minutes	A	
Y	50	100 A/m	1 Minutes	A	
Z	50	100 A/m	1 Minutes	A	
X	50	1000 A/m	1 sec	A	
Y	50	1000 A/m	1 sec	A	
Z	50	1000 A/m	1 sec	A	

Additional Notes: A=criteria A, B=criteria B, C=criteria C

--

13.3 Test Setup Photo



14. Appendix

14.1 Appendix A: Test Equipment

14.1.1 Test Equipment List

Location Con03	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 03	EMI Receiver 13	ROHDE & SCHWARZ	ESCI	101015	07/25/2019	07/25/2020
Conduction 03	LISN 15	R&S	ENV216	101335	11/22/2018	11/22/2019
Conduction 03	LISN 22	R&S	ENV216	101478	08/13/2019	08/13/2020
Conduction 03	Conduction 03 -1 Cable	WOKEN	CFD 300-NL	Conduction 03 -1	08/23/2019	08/23/2020

Location Chamber02	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Radiation (Chamber02)	BILOG Antenna 17	Schwarzbeck	Schwarzbeck VULB 9168+EMCI-N -6-05	645	03/06/2019	03/06/2020
Radiation (Chamber02)	Preamplifier 25	EMCI	EMC9135	980295	02/27/2019	02/27/2020
Radiation (Chamber02)	Coaxial Cable Chmb 02-10M-02	EMC	RG214U	Chmb 02-10M-02	08/23/2019	08/23/2020
Radiation (Chamber02)	EMI Receiver 12	ROHDE & SCHWARZ	ESCI	100804	08/14/2019	08/14/2020

Location Chmb14	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Rad. Above 1GHz	Spectrum Analyzer 25	R&S	FSV 40	101499	11/03/2018	11/03/2019
Rad. Above 1GHz	Horn Antenna 06	ETS-Lindgren	3117	00066665	10/31/2018	10/31/2019
Rad. Above 1GHz	Preamplifier 13	MITEQ	JS44-0010180 0-25-10P-44	1329256	11/21/2018	11/21/2019
Rad. Above 1GHz	Microwave Cable 35	WOKEN	WCBA-WCA0 4NM.SM6	Chamber 14-1	01/31/2019	01/31/2020
Rad. Above 1GHz	Microwave Cable 36	WOKEN	WCBA-WCA0 4NM.SM0.8	Chamber 14-2	01/31/2019	01/31/2020

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
EN61K-4-2	ESD Gun 12	EM TEST	Dito	P1650188689	05/07/2019	05/07/2020
EN61K-4-3	Broadband Log-Periodic Antenna	AR	AT1080	310698	N/A	N/A
EN61K-4-3	Horn Antenna RF-01	AR	ATS700M11 G	0335864	N/A	N/A
EN61K-4-3	Amplifier 80Mz~1GHz 250W	AR	250W1000A	312494	N/A	N/A
EN61K-4-3	Amplifier 800MHz~4.2GHz 50W	AR	50S1G4M1	312762	N/A	N/A
EN61K-4-3	Amplifier 4.0~8.0GHz 35W	AR	35S4G8AM1	0335752	N/A	N/A
EN61K-4-3	Broadband Coupler 80M~1GHz	Amplifier Research	DC6180A	0341805	N/A	N/A
EN61K-4-3	Coaxial Cable	INSULATED	NPS-4806-23 60-NP3	108599.003.01.0 3	N/A	N/A
EN61K-4-3	Broadband Coupler 0.8G~4.26GHz	AR	DC7144A	0335226	N/A	N/A
EN61K-4-3	Broadband Coupler 4G~8GHz	AR	DC7350A	0335817	N/A	N/A
EN61K-4-3	Signal Generator 07	ROHDE & SCHWARZ	SMB100A	107780	10/28/2018	10/28/2019
EN61K-4-4	EFT and SURGE Test System	EM TEST	UCS-500 M6B	V0728102674	02/14/2019	02/14/2020
EN61K-4-4	Capacitive Coupling Clamp	EM TEST	HFK	0907-106	02/14/2019	02/14/2020
EN61K-4-5	CDN-UTP8 ED3	EMC-PARTNER	CDN-UTP8	1509	04/02/2019	04/02/2020
EN61K-4-5	SURGE-TESTER	EMC Partner	MIG0603IN3	523	04/02/2019	04/02/2020
EN61K-4-6	CDN M2+M3 05	Frankonia	CDN M2+M3	A2210235/2013	09/22/2018	09/22/2019
EN61K-4-6	Coaxial Cable 4-6 02-1			4-6 02-1	N/A	N/A
EN61K-4-6	Conducted Immunity Test System 02	Frankonia	CIT-10-75-D C	126B1301/2014	03/25/2019	03/25/2020
EN61K-4-6	EM-Clamp	Schaffner	KEMZ-801	19215	11/08/2018	11/08/2019
EN61K-4-8	Magnetic Field Immunity Loop	FCC	F-1000-4-8-L-1M	01037	05/27/2019	06/05/2020
EN61K-4-8	Magnetic Field Test Generator	FCC	F-1000-4-8-G -125A	01038	05/27/2019	06/05/2020

PS: N/A => The equipment does not need calibration.

****Software for Controlling Spectrum/Receiver and Calculating Test Data**

Test Item	Filename	Version
EN61000-4-2	N/A	2.0
EN61000-4-3	i2	4.130102k
EN61000-4-4	EMC TEST	4.10
EN61000-4-5	EMC TEST	4.10
EN61000-4-6	FRANKONIA CD-LAB	V5.221
EN61000-4-8	N/A	

Site	Filename	Version	Issue Date
Conduction/Radiation	EZ EMC	ISL-03A2	3/6/2013

14.2 Appendix B: Uncertainty of Measurement

The laboratory measurement uncertainty accordance with refers to CISPR 16-4-2. If U_{lab} is less than or equal to U_{cispr} in Table 1, then the test report may either state the value of U_{lab} or state that U_{lab} is less than U_{cispr} .

The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 03>

AMN: ± 2.90 dB

<Chamber 02 (10M)>

Horizontal

30MHz~200MHz: ± 4.69 dB

200MHz~1000MHz: ± 4.30 dB

Vertical

30MHz~200MHz: ± 4.65 dB

200MHz~1000MHz: ± 4.35 dB

<Chamber 14 (3M)>

1GHz~6GHz: ± 5.12 dB

<Immunity 02>

Test item	Uncertainty	Test item	Uncertainty
EN 61000-4-2 (ESD)		EN 61000-4-6 (CS)	
Rise time tr	$\leq 15\%$	CDN	$\pm 1.36\text{dB}$
Peak current Ip	$\leq 6.3\%$	EM Clamp	$\pm 3.19\text{dB}$
current at 30 ns	$\leq 6.3\%$	EN 61000-4-8 (Magnetic)	$\pm 6.55\%$
current at 60 ns	$\leq 6.3\%$		
EN 61000-4-3 (RS)	$\pm 2.19\text{dB}$		
EN 61000-4-4 (EFT)			
voltage rise time (tr)	$\pm 6.2\%$		
peak voltage value (VP)	$\pm 8.6\%$		
voltage pulse width (tw)	$\pm 5.9\%$		
EN 61000-4-5 (Surge)			
open-circuit voltage front time	$\pm 1.2\mu\text{s}$		
open-circuit voltage peak value	$\pm 8.6\%$		
open-circuit voltage duration (Td)	$\pm 50.7\mu\text{s}$		

14.3 Appendix C: Photographs of EUT

Please refer to the File of **ISL-19LE557P-1-MA**

Certificate

Issue Date: December 6, 2019
 Ref. Report No. ISL-19LE557CE35-1-MA

Product Name : THN 10 Series
 Model(s) : THN 10-2410WIRzzzzz; THN 10-2411WIRzzzzz; THN 10-2412WIRzzzzz;
 THN 10-2413WIRzzzzz; THN 10-2415WIRzzzzz; THN 10-2421WIRzzzzz;
 THN 10-2422WIRzzzzz; THN 10-2423WIRzzzzz; THN 10-2425WIRzzzzz;
 THN 10-4810WIRzzzzz; THN 10-4811WIRzzzzz; THN 10-4812WIRzzzzz;
 THN 10-4813WIRzzzzz; THN 10-4815WIRzzzzz; THN 10-4821WIRzzzzz;
 THN 10-4822WIRzzzzz; THN 10-4823WIRzzzzz; THN 10-4825WIRzzzzz;
 THN 10-7210WIRzzzzz; THN 10-7211WIRzzzzz; THN 10-7212WIRzzzzz;
 THN 10-7213WIRzzzzz; THN 10-7215WIRzzzzz; THN 10-7221WIRzzzzz;
 THN 10-7222WIRzzzzz; THN 10-7223WIRzzzzz; THN 10-7225WIRzzzzz;
 z can be any alphanumeric or dash or blank



Brand : TRACO POWER
 Responsible Party : TRACO ELECTRONIC AG
 Address : Sihlbruggstrasse 111 CH-6340 Baar Switzerland

We, International Standards Laboratory Corp., hereby certify that:

The sample ISL received which bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in European Council Directive EMC Directive 2014/30/EU. And Our laboratories is the accredited laboratories and are approved according to ISO/IEC 17025. The device was passed the test performed according to :



Standards:

EN 55032:2015+AC: 2016, CISPR 32: 2015+COR1:2016: Class A

AS/NZS CISPR 32:2015: Class A

EN 55035: 2017 and CISPR 35: 2016

EN 61000-4-2: 2009 and IEC 61000-4-2: 2008

EN 61000-4-3: 2006+A1: 2008 +A2: 2010 and

IEC 61000-4-3: 2006+A1: 2007+A2: 2010

EN 61000-4-4: 2012 and IEC 61000-4-4:2012

EN 61000-4-5: 2014+A1:2017 and IEC 61000-4-5: 2014+A1:2017

EN 61000-4-6: 2014+AC: 2015 and IEC 61000-4-6:2013

EN 61000-4-8: 2010 and IEC 61000-4-8: 2009

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The determination of the test results is determined by customer agreement, regulations or standard document specifications.

The Laboratory evaluates measurement inaccuracies based on regulatory or standard document specifications and is listed in the report for reference. The quantitative project part judges the conformity of the test results based on the evaluation results of the standard cited uncertainty, and the qualitative project does not temporarily evaluate the measurement uncertainty.

Angus Chu
 Angus Chu / Director



International Standards Laboratory Corp.

LT LAB:

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan
 Tel: 886-3-407-1718; Fax: 886-3-407-1738

CE MARK TECHNICAL FILE

AS/NZS EMC CONSTRUCTION FILE

of

Product Name

THN 10 Series

Model

**THN 10-2410WIRzzzzz; THN 10-2411WIRzzzzz; THN
10-2412WIRzzzzz; THN 10-2413WIRzzzzz; THN
10-2415WIRzzzzz; THN 10-2421WIRzzzzz; THN
10-2422WIRzzzzz; THN 10-2423WIRzzzzz; THN
10-2425WIRzzzzz; THN 10-4810WIRzzzzz; THN
10-4811WIRzzzzz; THN 10-4812WIRzzzzz; THN
10-4813WIRzzzzz; THN 10-4815WIRzzzzz; THN
10-4821WIRzzzzz; THN 10-4822WIRzzzzz; THN
10-4823WIRzzzzz; THN 10-4825WIRzzzzz; THN
10-7210WIRzzzzz; THN 10-7211WIRzzzzz; THN
10-7212WIRzzzzz; THN 10-7213WIRzzzzz; THN
10-7215WIRzzzzz; THN 10-7221WIRzzzzz; THN
10-7222WIRzzzzz; THN 10-7223WIRzzzzz; THN
10-7225WIRzzzzz;**
z can be any alphanumeric or dash or blank

Brand



Contains:

1. Declaration of Conformity
2. EN 55032/CISPR 32, AS/NZS CISPR 32 EMI test report
3. EN 55035/CISPR 35, test report
4. Block Diagram and Schematics
5. Users' manual

Declaration of Conformity

Name of Responsible Party: TRACO ELECTRONIC AG

Address of Responsible Party: Sihlbruggstrasse 111 CH-6340 Baar Switzerland

Declares that product: THN 10 Series

Model: THN 10-2410WIRzzzzzz; THN 10-2411WIRzzzzzz;
THN 10-2412WIRzzzzzz; THN 10-2413WIRzzzzzz;
THN 10-2415WIRzzzzzz; THN 10-2421WIRzzzzzz;
THN 10-2422WIRzzzzzz; THN 10-2423WIRzzzzzz;
THN 10-2425WIRzzzzzz; THN 10-4810WIRzzzzzz;
THN 10-4811WIRzzzzzz; THN 10-4812WIRzzzzzz;
THN 10-4813WIRzzzzzz; THN 10-4815WIRzzzzzz;
THN 10-4821WIRzzzzzz; THN 10-4822WIRzzzzzz;
THN 10-4823WIRzzzzzz; THN 10-4825WIRzzzzzz;
THN 10-7210WIRzzzzzz; THN 10-7211WIRzzzzzz;
THN 10-7212WIRzzzzzz; THN 10-7213WIRzzzzzz;
THN 10-7215WIRzzzzzz; THN 10-7221WIRzzzzzz;
THN 10-7222WIRzzzzzz; THN 10-7223WIRzzzzzz;
THN 10-7225WIRzzzzzz;
z can be any alphanumeric or dash or blank



Brand: TRACO POWER

Assembled by: Same as above

Address: Same as above

Conforms to the EMC Directive 2014/30/EU as attested by conformity with the following harmonized standards:

EN 55032:2015+AC:2016, CISPR 32: 2015+COR1:2016: Class A:
Electromagnetic compatibility of multimedia equipment - Emission
requirements.

AS/NZS CISPR 32:2015: Class A: Electromagnetic compatibility of multimedia
equipment- Emission requirements

Performed Item	Test Performed	Deviation	Result
Conducted emissions from the AC mains power ports	Yes	No	PASS
Telecommunication Port Conducted Emissions (asymmetric mode)	N/A	N/A	N/A
Radiated emissions at frequencies below 1 GHz	Yes	No	PASS
Radiated emissions at frequencies above 1 GHz	Yes	No	PASS
Radiated emissions from FM receivers	N/A	N/A	N/A
Voltage Disturbance Emissions at Antenna Terminals	N/A	N/A	N/A
Differential voltage emissions	N/A	N/A	N/A
Outdoor units of home satellite receiving systems	N/A	N/A	N/A

<to be continued>

EN 55035:2017 and CISPR 35:2016: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008+A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4:2012 IEC 61000-4-4:2012	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5:2014+A1:2017 IEC 61000-4-5:2014+A1:2017	Surge	Pass	B
EN 61000-4-6:2014+AC:2015 IEC 61000-4-6:2013	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11:2004+A1:2017 IEC 61000-4-11:2004+A1:2017	Voltage Dips / Short Interruption and Voltage Variation		
	>95% in 0.5 cycle	N/A	B
	30% in 25 cycle	N/A	C
	>95% in 250 cycle	N/A	C

Standard	Description	Results
EN 61000-3-2:2014 IEC 61000-3-2:2014	Limits for harmonics current emissions	N/A
EN 61000-3-3:2013 IEC 61000-3-3:2013	Limits for voltage fluctuations and flicker in low-voltage supply systems.	N/A

We, TRACO ELECTRONIC AG, hereby declare that the equipment bearing the trade name and model number specified above was tested conforming to the applicable Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the requirements.

TRACO ELECTRONIC AG

Date: December 6, 2019

Declaration of Conformity

Name of Responsible Party: TRACO ELECTRONIC AG

Address of Responsible Party: Sihlbruggstrasse 111 CH-6340 Baar Switzerland

Declares that product: THN 10 Series

Model: THN 10-2410WIRzzzzzz; THN 10-2411WIRzzzzzz;
THN 10-2412WIRzzzzzz; THN 10-2413WIRzzzzzz;
THN 10-2415WIRzzzzzz; THN 10-2421WIRzzzzzz;
THN 10-2422WIRzzzzzz; THN 10-2423WIRzzzzzz;
THN 10-2425WIRzzzzzz; THN 10-4810WIRzzzzzz;
THN 10-4811WIRzzzzzz; THN 10-4812WIRzzzzzz;
THN 10-4813WIRzzzzzz; THN 10-4815WIRzzzzzz;
THN 10-4821WIRzzzzzz; THN 10-4822WIRzzzzzz;
THN 10-4823WIRzzzzzz; THN 10-4825WIRzzzzzz;
THN 10-7210WIRzzzzzz; THN 10-7211WIRzzzzzz;
THN 10-7212WIRzzzzzz; THN 10-7213WIRzzzzzz;
THN 10-7215WIRzzzzzz; THN 10-7221WIRzzzzzz;
THN 10-7222WIRzzzzzz; THN 10-7223WIRzzzzzz;
THN 10-7225WIRzzzzzz;
z can be any alphanumeric or dash or blank



Brand: TRACO POWER

Assembled by: Same as above

Address: Same as above

Conforms to the EMI part of RCM Mark requirements as attested by conformity with the following standards:

AS/NZS CISPR 32:2015: Class A: Electromagnetic compatibility of multimedia equipment- Emission requirements

We, TRACO ELECTRONIC AG, hereby declare that the equipment bearing the trade name and model number specified above was tested conforming to the applicable Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the requirements.

TRACO ELECTRONIC AG

Date: December 6, 2019

CE TEST REPORT

of
EN 55032 / CISPR 32 / AS/NZS CISPR 32
Class A
EN 55035 / CISPR 35 / IMMUNITY

Product : **THN 10 Series**

Model(s): **THN 10-2415WIRzzzzzz**

(more serial models listed on 1.3 of this test report)



Brand: **TRACO POWER**

Applicant: **TRACO ELECTRONIC AG**

Address: **Sihlbruggstrasse 111 CH-6340
Baar Switzerland**

Test Performed by:

International Standards Laboratory Corp.

<LT LAB>

*Address:

No. 120, Lane 180, Hsin Ho Rd.,
Lung-Tan Dist., Tao Yuan City 325, Taiwan
*Tel: 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-19LE557CE35-1-MA

Issue Date : December 6, 2019

This report totally contains 64 pages including this cover page and contents page.

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory Corp.

Contents of Report

1.	General	1
1.1	Certification of Accuracy of Test Data.....	1
1.2	Test Standards.....	2
1.3	Model Number Definition	5
1.4	Description of EUT	6
1.5	Description of Support Equipment	9
2.	Power Main Port Conducted Emissions	10
2.1	Test Setup and Procedure	10
2.2	Conduction Test Data: Configuration 1.....	12
2.3	Test Setup Photo.....	14
3.	Telecommunication Port Conducted Emissions	16
3.1	Test Setup and Procedure	16
4.	Radiated Disturbance Emissions.....	18
4.1	Test Setup and Procedure	18
4.2	Limit	20
4.3	Radiation Test Data: Configuration 1.....	22
4.4	Test Setup Photo.....	26
5.	Voltage Disturbance Emissions at Antenna Terminals	28
5.1	Test Setup and Procedure	28
6.	Differential Voltage Emissions.....	30
6.1	Test Setup and Procedure	30
7.	Outdoor units of home satellite receiving systems	32
7.1	Test Setup and Procedure	32
8.	Electrostatic discharge (ESD) immunity	34
8.1	Test Specification and Setup	34
8.2	Test Data: Configuration 1	35
8.3	Test Point.....	36
8.4	Test Setup Photo.....	37
9.	Radio-Frequency, Electromagnetic Field immunity.....	38
9.1	Test Specification and Setup	38
9.2	Test Data: Configuration 1	39
9.3	Test Setup Photo.....	41
10.	Electrical Fast transients/burst immunity.....	42
10.1	Test Specification and Setup	42
10.2	Test Data: Configuration 1	44
10.3	Test Setup Photo.....	46
11.	Surge Immunity	47
11.1	Test Specification and Setup	47
11.2	Test Data: Configuration 1	48
11.3	Test Setup Photo.....	49
12.	Immunity to Conductive Disturbance.....	50
12.1	Test Specification and Setup	50
12.2	Test Data: Configuration 1	51
12.3	Test Setup Photo.....	52
13.	Power Frequency Magnetic Field immunity.....	53
13.1	Test Specification and Setup	53
13.2	Test Data: Configuration 1	54
13.3	Test Setup Photo.....	55

14. Appendix.....	56
14.1 Appendix A: Test Equipment.....	56
14.2 Appendix B: Uncertainty of Measurement	59
14.3 Appendix C: Photographs of EUT Please refer to the File of ISL-19LE557P-1-MA.	61

1. General

1.1 Certification of Accuracy of Test Data

Standards: Please refer to 1.2

Equipment Tested: THN 10 Series

Model: THN 10-2415WIRzzzzzz
(more serial models listed on 1.3 of this test report)



Brand: TRACO POWER

Applicant: TRACO ELECTRONIC AG

Sample received Date: August 31, 2019

Final test Date: EMI: refer to the date of test data

EMS: September 18, 2019

Test Site: Chamber 02; Chamber 14; Conduction 03; Immunity 02

Test Distance: 10M; 3M (above 1GHz) (EMI test)

Temperature: refer to each site test data

Humidity: refer to each site test data

Atmospheric Pressure: 86 kPa to 106 kPa

Input power: Conduction input power: DC 24 V

Radiation input power: DC 24 V

Immunity input power: DC 24 V

Test Result: PASS

Report Engineer: Cheryl Tung

Test Engineer:

Hasan Yu
Hasan Yu

Approved By:

Angus Chu
Angus Chu / Director

1.2 Test Standards

The tests which this report describes were conducted by an independent electromagnetic compatibility consultant, International Standards Laboratory Corp. in accordance with the following

EN 55032:2015+AC:2016, CISPR 32: 2015+COR1:2016: Class A: Electromagnetic compatibility of multimedia equipment - Emission requirements.

AS/NZS CISPR 32:2015: Class A: Electromagnetic compatibility of multimedia equipment- Emission requirements

Performed Item	Test Performed	Deviation	Result
Conducted emissions from the AC mains power ports	Yes	No	PASS
Telecommunication Port Conducted Emissions (asymmetric mode)	N/A	N/A	N/A
Radiated emissions at frequencies below 1 GHz	Yes	No	PASS
Radiated emissions at frequencies above 1 GHz	Yes	No	PASS
Radiated emissions from FM receivers	N/A	N/A	N/A
Voltage Disturbance Emissions at Antenna Terminals	N/A	N/A	N/A
Differential voltage emissions	N/A	N/A	N/A
Outdoor units of home satellite receiving systems	N/A	N/A	N/A

EN 55035:2017 and CISPR 35:2016: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4:2012 IEC 61000-4-4:2012	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5:2014+A1:2017 IEC 61000-4-5:2014+A1:2017	Surge	Pass	B
EN 61000-4-6:2014+AC:2015 IEC 61000-4-6:2013	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11:2004+A1:2017 IEC 61000-4-11:2004+A1:2017	Voltage Dips / Short Interruption and Voltage Variation		
	>95% in 0.5 cycle	N/A	B
	30% in 25 cycle	N/A	C
	>95% in 250 cycle	N/A	C

Standard	Description	Results
EN 61000-3-2:2014 IEC 61000-3-2:2014	Limits for harmonics current emissions	N/A
EN 61000-3-3:2013 IEC 61000-3-3:2013	Limits for voltage fluctuations and flicker in low-voltage supply systems.	N/A

1.2.1 Performance Criteria for Compliance: EN 55024

Performance criterion A

During and after the test the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a minimum performance level specified by the manufacturer when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion B

After the test, the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion C

During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.

Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

1.3 Model Number Definition

There are more than one model number for this product, please refer the details listed below:

THN 10-2410WIRzzzzzz; THN 10-2411WIRzzzzzz; THN 10-2412WIRzzzzzz; THN

10-2413WIRzzzzzz; THN 10-2415WIRzzzzzz; THN 10-2421WIRzzzzzz; THN

10-2422WIRzzzzzz; THN 10-2423WIRzzzzzz; THN 10-2425WIRzzzzzz; THN

10-4810WIRzzzzzz; THN 10-4811WIRzzzzzz; THN 10-4812WIRzzzzzz; THN

10-4813WIRzzzzzz; THN 10-4815WIRzzzzzz; THN 10-4821WIRzzzzzz; THN

10-4822WIRzzzzzz; THN 10-4823WIRzzzzzz; THN 10-4825WIRzzzzzz; THN

10-7210WIRzzzzzz; THN 10-7211WIRzzzzzz; THN 10-7212WIRzzzzzz; THN

10-7213WIRzzzzzz; THN 10-7215WIRzzzzzz; THN 10-7221WIRzzzzzz; THN

10-7222WIRzzzzzz; THN 10-7223WIRzzzzzz; THN 10-7225WIRzzzzzz;

z can be any alphanumeric or dash or blank

1.4 Description of EUT

EUT

This report test data using the report number 19LE557CE35-1

Description	THN 10 Series
Condition	Pre-Production
Model	THN 10-2415WIRzzzzz (more serial models listed on 1.3 of this test report)
Serial Number	N/A
Highest working frequency:	395kHz

Test configuration:

Configuration	Model Name	Input VDC	Output Voltage VDC	Output Current mA
1	THN 10-2415WIRzzzzz	24	24	420

For EMS (Not Include Electrical Fast transients/burst immunity & Surge Immunity) test

Configuration	Model Name	Input VDC	Output Voltage VDC	Output Current mA	With an aluminum electrolytic capacitor test board
1	THN 10-2415WIRzzzzz	24	24	420	No

For Electrical Fast transients/burst immunity & Surge Immunity test mode

Configuration	Model Name	Input VDC	Output Voltage VDC	Output Current mA	With an aluminum electrolytic capacitor test board
1	THN 10-2415WIRzzzzz	24	24	420	Yes

Different Model list:

Model Name	Input Range (VDC)	Output Voltage (VDC)	Output Current@Full Load (mA)
THN 10-2410WIRzzzzzz	9 ~ 36	3.3	3000
THN 10-2411WIRzzzzzz	9 ~ 36	5	2000
THN 10-2412WIRzzzzzz	9 ~ 36	12	830
THN 10-2413WIRzzzzzz	9 ~ 36	15	670
THN 10-2415WIRzzzzzz	9 ~ 36	24	420
THN 10-2421WIRzzzzzz	9 ~ 36	±5	±1000
THN 10-2422WIRzzzzzz	9 ~ 36	±12	±416
THN 10-2423WIRzzzzzz	9 ~ 36	±15	±333
THN 10-2425WIRzzzzzz	9 ~ 36	±24	±210
THN 10-4810WIRzzzzzz	18 ~ 75	3.3	3000
THN 10-4811WIRzzzzzz	18 ~ 75	5	2000
THN 10-4812WIRzzzzzz	18 ~ 75	12	830
THN 10-4813WIRzzzzzz	18 ~ 75	15	670
THN 10-4815WIRzzzzzz	18 ~ 75	24	420
THN 10-4821WIRzzzzzz	18 ~ 75	±5	±1000
THN 10-4822WIRzzzzzz	18 ~ 75	±12	±416
THN 10-4823WIRzzzzzz	18 ~ 75	±15	±333
THN 10-4825WIRzzzzzz	18 ~ 75	±24	±210

Model Name	Input Range (VDC)	Output Voltage (VDC)	Output Current@Full Load (mA)
THN 10-7210WIRzzzzzz	36 ~ 160	3.3	3000
THN 10-7211WIRzzzzzz	36 ~ 160	5	2000
THN 10-7212WIRzzzzzz	36 ~ 160	12	830
THN 10-7213WIRzzzzzz	36 ~ 160	15	670
THN 10-7215WIRzzzzzz	36 ~ 160	24	420
THN 10-7221WIRzzzzzz	36 ~ 160	±5	±1000
THN 10-7222WIRzzzzzz	36 ~ 160	±12	±416
THN 10-7223WIRzzzzzz	36 ~ 160	±15	±333
THN 10-7225WIRzzzzzz	36 ~ 160	±24	±210
z can be any alphanumeric or dash or blank			

EMI Noise Source:

Please refer to the technical documents.

EMI Solution:

Please refer to the technical documents.


1.5 Description of Support Equipment

No	Unit	Model Serial No.	Brand	Power Cord	FCC ID
1	DC Power Source	GPD-4050D S/N: N/A	GW INSTEK	Non-shielded	FCC DOC
2	Dummy Load	N/A S/N: N/A	N/A	N/A	N/A

2. Power Main Port Conducted Emissions

2.1 Test Setup and Procedure

2.1.1 Test Setup



2.1.2 Test Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, live and neutral, were measured. All of the interface cables were manipulated according to EN 55032 requirements.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

2.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150kHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9kHz

2.1.4 Limit

Conducted emissions from the DC mains power ports of Class A equipment:

Frequency	QP	AV
MHz	dB(μV)	dB(μV)
0.15-0.50	79	66
5.0-30	73	60
Note: The lower limit shall apply at the transition frequencies		


Conducted emissions from the DC mains power ports of Class B equipment:

Frequency	QP	AV
MHz	dB(μV)	dB(μV)
0.15-0.50	66-56	56-46
0.50-5.0	56	46
5.0-30	60	50
Note: The lower limit shall apply at the transition frequencies		

Customers require testing for DC products, non-regulatory requirements.

2.2 Conduction Test Data: Configuration 1

-Live



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP_Emission (dBuV)	QP_Limit (dBuV)	QP_Margin (dB)	AVG_Emission (dBuV)	AVG_Limit (dBuV)	AVG_Margin (dB)
1	0.354	49.26	49.53	10.14	59.40	79.00	-19.60	59.67	66.00	-6.33
2	0.710	44.79	45.01	10.17	54.96	73.00	-18.04	55.18	60.00	-4.82
3	1.062	40.45	40.73	10.17	50.62	73.00	-22.38	50.90	60.00	-9.10
4	1.770	41.46	41.70	10.21	51.67	73.00	-21.33	51.91	60.00	-8.09
5	2.830	39.93	40.20	10.27	50.20	73.00	-22.80	50.47	60.00	-9.53
6	3.890	40.57	40.65	10.31	50.88	73.00	-22.12	50.96	60.00	-9.04

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor


Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

- Neutral



No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.354	49.86	50.13	10.14	60.00	79.00	-19.00	60.27	66.00	-5.73
2	0.706	45.46	45.72	10.17	55.63	73.00	-17.37	55.89	60.00	-4.11
3	1.062	42.55	42.83	10.18	52.73	73.00	-20.27	53.01	60.00	-6.99
4	1.414	43.04	43.30	10.20	53.24	73.00	-19.76	53.50	60.00	-6.50
5	3.890	42.42	42.55	10.31	52.73	73.00	-20.27	52.86	60.00	-7.14
6	4.246	42.47	42.61	10.32	52.79	73.00	-20.21	52.93	60.00	-7.07
7	4.954	42.91	42.84	10.35	53.26	73.00	-19.74	53.19	60.00	-6.81
8	6.014	42.51	42.73	10.39	52.90	73.00	-20.10	53.12	60.00	-6.88

Note:

Margin = QP/AVG Emission - Limit

QP/AVG Emission = QP_R/AVG_R + Correct Factor

Correct Factor = LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit


 The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.
 If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.3 Test Setup Photo

Front View




Back View



3. Telecommunication Port Conducted Emissions

3.1 Test Setup and Procedure

3.1.1 Test Setup



3.1.2 Test Procedure

The measurements are performed in a shielded room test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

The EUT, any support equipment, and any interconnecting cables were arranged and moved to get the maximum measurement. All of the interface cables were manipulated according to EN 55032 requirements.

The port of the EUT was connected to the support equipment through the ISN and linked in normal condition.

DC input power for the EUT & the support equipment power outlets were obtained from the same filtered source that provided input power to the LISN.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information could be useful in reducing their amplitude.

3.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150kHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9kHz

3.1.4 Limit

Asymmetric mode conducted emissions from Class_A equipment:

Applicable to

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. antenna ports.

Frequency range MHz	Coupling device	Detector type / bandwidth	Class_A voltage limits dB(μV)	Class_A current limits dB(μA)	
0.15-0.5	AAN	Quasi Peak / 9 kHz	97-87	n/a	
0.5-30			87		
0.15-0.5	AAN	Average / 9 kHz	84-74	n/a	
0.5-30			74		
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	97-87	53-43	
0.5-30			87	43	
0.15-0.5	CVP and current probe	Average / 9 kHz	84-74	40-30	
0.5-30			74	30	
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	53-43	
0.5-30				43	
0.15-0.5	Current Probe	Average / 9 kHz		40-30	
0.5-30				30	

Asymmetric mode conducted emissions from Class_B equipment:

Applicable to:

1. wired network ports.
2. optical fibre ports with metallic shield or tension members.
3. broadcast receiver tuner ports.
4. antenna ports.




Frequency range MHz	Coupling device	Detector type / bandwidth	Class_B voltage limits dB(μV)	Class_B current limits dB(μA)	
0.15-0.5	AAN	Quasi Peak / 9 kHz	84-74	n/a	
0.5-30			74		
0.15-0.5	AAN	Average / 9 kHz	74-64	n/a	
0.5-30			64		
0.15-0.5	CVP and current probe	Quasi Peak / 9 kHz	84-74	40-30	
0.5-30			74	30	
0.15-0.5	CVP and current probe	Average / 9 kHz	74-64	30-20	
0.5-30			64	20	
0.15-0.5	Current Probe	Quasi Peak / 9 kHz	n/a	40-30	
0.5-30				30	
0.15-0.5	Current Probe	Average / 9 kHz		30-20	
0.5-30				20	

****Remarks: It is not necessary to be tested on this item.**

4. Radiated Disturbance Emissions

4.1 Test Setup and Procedure

4.1.1 Test Setup



The 3dB beam width of the horn antenna used for the test is as shown in the table below.

Frequency (GHz)	E-plane	H-plane	$\theta_{3\text{dB}}(\text{min})$	d= 3 m
				w (m)
1	88°	147°	88°	5.79
2	68°	119°	68°	4.04
3	73°	92°	73°	4.44
4	70°	89°	70°	4.20
5	55°	60°	55°	3.12
6	63°	62°	62°	3.60

4.1.2 Test Procedure

The radiated emissions test will then be repeated on the open site or chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter open field sites or 10 meter chamber. Desktop EUT are set up on a FRP stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 6 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. All of the interface cables were manipulated according to EN 55032 requirements.

The highest internal source of an EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes.

If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz.

If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.

If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.

If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.

4.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	30MHz--1000MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz
Frequency Range:	Above 1 GHz to 6 GHz
Detector Function:	Peak/Average Mode
Resolution Bandwidth:	1MHz

4.2 Limit

Radiated emissions at frequencies up to 1 GHz for Class A equipment:

Frequency range MHz	Measurement		Class_A limits dB(μ V/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	40
230-1000			47
30-230	3	Peak / 1MHz	50
230-1000			57

Radiated emissions at frequencies above 1 GHz for Class A equipment:

Frequency range MHz	Measurement		Class_A limits dB(μ V/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	56
3000-6000			60
1000-3000		Peak / 1MHz	76
3000-6000			80

Radiated emissions at frequencies up to 1 GHz for Class B equipment:

Frequency range MHz	Measurement		Class_B limits dB(μ V/m)
	Distance m	Detector type / bandwidth	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	30
230-1000			37
30-230	3	Peak / 1MHz	40
230-1000			47

Radiated emissions at frequencies above 1 GHz for Class_B equipment:


Frequency range MHz	Measurement		Class_B limits dB(μV/m)
	Distance m	Detector type / bandwidth	FSOATS
1000-3000	3	Average / 1MHz	50
3000-6000		Peak / 1MHz	54
1000-3000	3	Peak / 1MHz	70
3000-6000			74

Radiated emissions from FM receivers:

Frequency range MHz	Measurement		Class_B limits dB(μV/m)	
	Distance m	Detector type / bandwidth	Fundamental	Harmonics
			OATS/SAC	OATS/SAC
30-230	10	Quasi Peak / 120 kHz	50	42
230-300				42
300-1000				46
30-230	3	Quasi Peak / 120 kHz	60	52
230-300				52
300-1000				56

4.3 Radiation Test Data: Configuration 1

- Radiated Emissions (Horizontal)



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	399.57	47.14	-12.14	35.00	47.00	-12.00	200	33	peak
2	549.92	41.89	-9.33	32.56	47.00	-14.44	300	295	peak
3	575.14	42.74	-8.59	34.15	47.00	-12.85	400	300	peak
4	600.36	45.28	-7.73	37.55	47.00	-9.45	400	163	peak
5	825.40	33.89	-4.17	29.72	47.00	-17.28	300	258	peak
6	941.80	31.80	-2.49	29.31	47.00	-17.69	200	359	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan.
 Tel: 03-4071718



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1200.00	60.07	-15.62	44.45	76.00	-31.55	229	0	peak
2	1275.00	58.06	-15.36	42.70	76.00	-33.30	200	344	peak
3	1400.00	59.67	-15.78	43.89	76.00	-32.11	200	332	peak
4	1525.00	60.59	-16.25	44.34	76.00	-31.66	200	326	peak
5	1575.00	61.05	-16.02	45.03	76.00	-30.97	200	342	peak
6	1650.00	58.68	-15.14	43.54	76.00	-32.46	146	360	peak

* Note:

Margin = Emission – Limit


Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

-Radiated Emissions (Vertical)


Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	53.28	45.57	-17.00	28.57	40.00	-11.43	100	317	peak
2	136.70	47.67	-17.06	30.61	40.00	-9.39	100	78	peak
3	400.54	47.52	-12.12	35.40	47.00	-11.60	400	130	peak
4	524.70	44.81	-9.58	35.23	47.00	-11.77	100	27	peak
5	575.14	45.09	-8.59	36.50	47.00	-10.50	100	267	peak
6	600.36	46.25	-7.73	38.52	47.00	-8.48	100	13	peak
7	800.18	38.61	-4.48	34.13	47.00	-12.87	100	109	peak
8	906.88	43.87	-3.05	40.82	47.00	-6.18	100	60	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain


A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.



Address: No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan.
 Tel: 03-4071718



Mk.	Frequency (MHz)	RX_R (dBuV)	Correct Factor(dB/m)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1200.00	59.25	-15.62	43.63	76.00	-32.37	100	318	peak
2	1600.00	57.82	-15.86	41.96	76.00	-34.04	193	360	peak
3	2465.00	55.16	-11.76	43.40	76.00	-32.60	181	360	peak
4	2600.00	53.81	-11.38	42.43	76.00	-33.57	139	360	peak
5	2950.00	53.00	-11.15	41.85	76.00	-34.15	176	360	peak
6	3000.00	52.26	-11.04	41.22	76.00	-34.78	200	317	peak

* Note:

Margin = Emission – Limit

Emission = Radiated Amplitude + Correct Factor

Correct Factor = Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Antenna Distance: 3 meters


Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

4.4 Test Setup Photo


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)




Back View (above 1GHz)



5. Voltage Disturbance Emissions at Antenna Terminals

5.1 Test Setup and Procedure

5.1.1 Test Setup



5.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dBuV at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

5.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

5.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.

Table clause	Frequency range MHz	Detector type/bandwidth	Class B limits dB(μ V) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies \leq 1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300	For frequencies \geq 1 GHz	46	54	50	See c)
	300 – 1 000				52	
A12.4	30 – 300	Peak/ 1 MHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	


a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.
b) Tuner units (not the LNB) for satellite signal reception.
c) Frequency modulation audio receivers and PC tuner cards.
d) Frequency modulation car radios.
e) Applicable to EUs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.

****Remarks: It is not necessary to be tested on this item.**

6. Differential Voltage Emissions

6.1 Test Setup and Procedure

6.1.1 Test Setup



6.1.2 Test Procedure

The output level of the auxiliary signal generator was set to 70dB_{UV} at the EUT antenna terminal with 75 ohms impedance with an un-modulated carrier.

The highest emissions were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The power of EUT was switched off to make sure the emission was not contributed by the auxiliary signal generator. While doing so, the interconnecting cables and major parts of the system were moved around to maximize the emission.

6.1.3 EMI Receiver Configuration (for the frequencies tested)

Frequency Range:	30MHz-2150MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz

6.1.4 Limit

Applicable to:

1. TV broadcast receiver tuner ports with an accessible connector.
2. RF modulator output ports.
3. FM broadcast receiver tuner ports with an accessible connector.

Table clause	Frequency range MHz	Detector type/bandwidth	Class B limits dB(μ V) 75 Ω			Applicability
			Other	Local Oscillator Fundamental	Local Oscillator Harmonics	
A12.1	30 – 950	For frequencies \leq 1 GHz	46	46	46	See a)
	950 – 2 150		46	54	54	
A12.2	950 – 2 150	Quasi Peak/ 120 kHz	46	54	54	See b)
A12.3	30 – 300	For frequencies \geq 1 GHz	46	54	50	See c)
	300 – 1 000				52	
A12.4	30 – 300	Peak/ 1 MHz	46	66	59	See d)
	300 – 1 000				52	
A12.5	30 – 950	Peak/ 1 MHz	46	76	46	See e)
	950 – 2 150			n/a	54	


a) Television receivers (analogue or digital), video recorders and PC TV broadcast receiver tuner cards working in channels between 30 MHz and 1 GHz, and digital audio receivers.
b) Tuner units (not the LNB) for satellite signal reception.
c) Frequency modulation audio receivers and PC tuner cards.
d) Frequency modulation car radios.
e) Applicable to EUs with RF modulator output ports (for example DVD equipment, video recorders, camcorders and decoders etc.) designed to connect to TV broadcast receiver tuner ports.

****Remarks: It is not necessary to be tested on this item.**

7. Outdoor units of home satellite receiving systems

7.1 Test Setup and Procedure

7.1.1 Test Setup



7.1.2 Test Procedure

The input signal shall be adjusted to get the maximum rated output level from the EUT. For the measurement in the frequency range from 30 MHz to 18 GHz the input signal shall be adjusted so that the output frequency is within this frequency range. For the measurement in the frequency range above 1 GHz, the frequency of the input signal shall be adjusted in such a way that the EUT is measured, as a minimum, at the lowest, middle and highest rated output frequency within the measured frequency range.

7.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	30MHz--1000MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120kHz
Frequency Range:	Above 1000MHz
Detector Function:	Peak/Average Mode
Resolution Bandwidth:	1MHz

7.1.4 Limit

Table Clause	Frequency Range MHz	Measurement			Class B Limits	Applicable to
		Facility (see Table A.1)	Distance m	Detector type / Bandwidth		
A7.1	30 to 1 000	SAC / OATS / FAR	See Table A.4	Quasi Peak / 120 kHz	See Table A.4	
A7.2	1 000 to 2 500	FSOATS	3	Average / 1 MHz	50 dB(μ V/m)	LO leakage and spurious radiated emissions from the EUT, in the region outside $\pm 7^\circ$ of the main beam axis. See Figure H.1
	2 500 to 18 000				64 dB(μ V/m)	
A7.3	1 000 to 18 000	FSOATS	3	Average / 1 MHz	37 dB(μ V/m)	LO leakage from the EUT, in the region within $\pm 7^\circ$ of the main beam axis. See Figure H.1
A7.4	1 000 to 18 000	Conducted (Clause H.4)	n/a	Average / 1 MHz	30 dBpW	

For details of the EUT configuration, see Annex H.

For radiated emissions measurements at frequencies up to 1 GHz, the requirements defined in Table A.4 shall be satisfied.

Apply the appropriate limits across the entire frequency range.

Apply the limits defined in table Clause A7.1 and A7.2. Also apply the limits defined in either table Clause A7.3 or A7.4.

****Remarks: It is not necessary to be tested on this item.**

8. Electrostatic discharge (ESD) immunity

8.1 Test Specification and Setup

8.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-2/ IEC 61000-4-2 (details referred to Sec 1.2)
Test Level:	Air +/- 2 kV, +/- 4 kV, +/- 8 kV Contact +/- 4 kV, +/- 6 kV
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S7

Selected Test Point


Air: discharges were applied to slots, aperture or insulating surfaces. 10 single air discharges were applied to each selected points.

Contact: Total 200 discharges minimum were to the selected contact points.

Indirect Contact Points: 25 discharges were applied to center of one edge of VCP and each EUT side of HCP with 10 cm away from EUT.

8.1.2 Test Setup

EUT is 1m from the wall and other metallic structure. When Battery test mode is needed, a cable with one 470KΩ resistor at two rare ends is connected from metallic part of EUT and screwed to HCP.



8.1.3 Test Result

Performance of EUT complies with the given specification

8.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-2	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-10
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	EM TEST(Model: Dito)
Voltage/Freq.	24 Vdc	

A=criteria A, B=criteria B, C=criteria C

→ Blue arrow represent Air discharge point

→ Red arrow represent Contact discharge point

ND=No Discharge (No Arcing); Meets criteria but unable to obtain an electrostatic discharge (ESD) at this test point.

X=EUT DOES NOT meet the acceptance criteria

A=criteria A, B=criteria B, C=criteria C

Contact Discharge	Voltage kV 25 Discharge @ 1 PPS									Comments
Test Location	+4	-4	+6	-6						Comments
1	ND	ND	ND	ND						
2	ND	ND	ND	ND						
3	ND	ND	ND	ND						
4	ND	ND	ND	ND						
5	ND	ND	ND	ND						
Air Discharge	Voltage kV 10 Discharge @ 1 PPS									Comments
Test Location	+2	-2	+4	-4	+8	-8				Comments
1	ND	ND	ND	ND	A	A				
2	ND	ND	ND	ND	A	A				
3	ND	ND	ND	ND	A	A				
4	ND	ND	ND	ND	A	A				
5	ND	ND	ND	ND	A	A				
Indirect Discharge	Voltage kV 25 Discharge @ 1 PPS									Comments
Test Location	+4	-4	+6	-6						Comments
VCP Front	A	A	A	A						
VCP Right	A	A	A	A						
VCP Left	A	A	A	A						
VCP Back	A	A	A	A						
Test Location	+4	-4	+6	-6						Comments
HCP Front	A	A	A	A						
HCP Right	A	A	A	A						
HCP Left	A	A	A	A						
HCP Back	A	A	A	A						

Additional Notes: A=criteria A, B=criteria B, C=criteria C

8.3 Test Point

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.

Figure 1 : Test Point Assignments Discharge:






Figure 2 : Test Point Assignments Discharge:



8.4 Test Setup Photo



9. Radio-Frequency, Electromagnetic Field immunity


9.1 Test Specification and Setup

9.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-3/ IEC 61000-4-3 (details referred to Sec 1.2)
Test Level:	10 V/m
Modulation:	AM 1kHz 80%
Frequency range:	80 MHz~1 GHz 1800MHz, 2600MHz, 3500MHz, 5000MHz
Frequency Step:	1% of last step frequency
Dwell time:	3s
Polarization:	Vertical and Horizontal
EUT Azimuth Angle	<input checked="" type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input checked="" type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S8

9.1.2 Test Setup

The field sensor is placed at one calibration grid point to check the intensity of the established fields on both polarizations. EUT is adjusted to have each side of EUT face coincident with the calibration plane. A CCD camera and speakers are used to monitor the condition of EUT for the performance judgment.



9.1.3 Test Result

Performance of EUT complies with the given specification

9.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-3	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-18
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	Chamber 04
Voltage/Freq.	24 Vdc	

A=criteria A, B=criteria B, C=criteria C

EUT Angle	Frequency		Dwell time	Modulation	Level (V/m)	Antenna Polarization	EUT Status	Comments
	Range (MHz)	Steps %						
0°(front)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
90°(left)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
180°(back)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
270°(right)	80-1000	1	3s	80% @ 1kHz	10	Vertical	A	
0°(front)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	
90°(left)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	
180°(back)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	
270°(right)	80-1000	1	3s	80% @ 1kHz	10	Horizontal	A	
0°(front)	1800	1	3s	80% @ 1kHz	10	Vertical	A	
90°(left)	1800	1	3s	80% @ 1kHz	10	Vertical	A	
180°(back)	1800	1	3s	80% @ 1kHz	10	Vertical	A	
270°(right)	1800	1	3s	80% @ 1kHz	10	Vertical	A	
0°(front)	1800	1	3s	80% @ 1kHz	10	Horizontal	A	
90°(left)	1800	1	3s	80% @ 1kHz	10	Horizontal	A	
180°(back)	1800	1	3s	80% @ 1kHz	10	Horizontal	A	
270°(right)	1800	1	3s	80% @ 1kHz	10	Horizontal	A	
0°(front)	2600	1	3s	80% @ 1kHz	10	Vertical	A	
90°(left)	2600	1	3s	80% @ 1kHz	10	Vertical	A	
180°(back)	2600	1	3s	80% @ 1kHz	10	Vertical	A	
270°(right)	2600	1	3s	80% @ 1kHz	10	Vertical	A	

EUT Angle	Frequency		Dwell time	Modulation	Level (V/m)	Antenna Polarization	EUT Status	Comments
	Range (MHz)	Steps %						
0°(front)	2600	1	3s	80% @ 1kHz	10	Horizontal	A	
90°(left)	2600	1	3s	80% @ 1kHz	10	Horizontal	A	
180°(back)	2600	1	3s	80% @ 1kHz	10	Horizontal	A	
270°(right)	2600	1	3s	80% @ 1kHz	10	Horizontal	A	
0°(front)	3500	1	3s	80% @ 1kHz	10	Vertical	A	
90°(left)	3500	1	3s	80% @ 1kHz	10	Vertical	A	
180°(back)	3500	1	3s	80% @ 1kHz	10	Vertical	A	
270°(right)	3500	1	3s	80% @ 1kHz	10	Vertical	A	
0°(front)	3500	1	3s	80% @ 1kHz	10	Horizontal	A	
90°(left)	3500	1	3s	80% @ 1kHz	10	Horizontal	A	
180°(back)	3500	1	3s	80% @ 1kHz	10	Horizontal	A	
270°(right)	3500	1	3s	80% @ 1kHz	10	Horizontal	A	
0°(front)	5000	1	3s	80% @ 1kHz	10	Vertical	A	
90°(left)	5000	1	3s	80% @ 1kHz	10	Vertical	A	
180°(back)	5000	1	3s	80% @ 1kHz	10	Vertical	A	
270°(right)	5000	1	3s	80% @ 1kHz	10	Vertical	A	
0°(front)	5000	1	3s	80% @ 1kHz	10	Horizontal	A	
90°(left)	5000	1	3s	80% @ 1kHz	10	Horizontal	A	
180°(back)	5000	1	3s	80% @ 1kHz	10	Horizontal	A	
270°(right)	5000	1	3s	80% @ 1kHz	10	Horizontal	A	
Additional Notes: A=criteria A, B=criteria B, C=criteria C								

9.3 Test Setup Photo



10. Electrical Fast transients/burst immunity

10.1 Test Specification and Setup

10.1.1 Test Specification

Port:	DC mains
Basic Standard:	EN 61000-4-4/ IEC 61000-4-4 (details referred to Sec 1.2)
Test Level:	DC Power Port: +/- 2 kV
Rise Time:	5ns
Hold Time:	50ns
Burst Period:	300ms
Repetition Frequency:	5kHz
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S9

Test Procedure


The EUT was setup on a nonconductive table 0.1 m above a reference ground plane.

Test Points	Polarity	Result	Comment
Line	+	N	60 sec
	-	N	60 sec
Neutral	+	N	60 sec
	-	N	60 sec
Line to Neutral	+	N	60 sec
	-	N	60 sec

Note: 'N' means normal, the EUT function is correct during the test.

10.1.2 Test Setup

EUT is at least 50cm from the conductive structure.



10.1.3 Test Result

Performance of EUT complies with the given specification

10.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-4	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-10
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	EM TEST (Model: UCS-500 M6B)
Voltage/Freq.	24 Vdc	

A=criteria A, B=(criteria B, C=Criteria C

AC Power Port: DC Power Port: LAN Port: Telephone Port:

DC Power Port

Line Under Test	Voltage Level	Severity Level	Pulse Polarity	Burst Repetition Rate	Test Duration	EUT Status	Comments
Line	0.5kV	1	+	300ms / 5.0kHz	1 Minutes	A	
Line	0.5kV	1	-	300ms / 5.0kHz	1 Minutes	A	
Neutral	0.5kV	1	+	300ms / 5.0kHz	1 Minutes	A	
Neutral	0.5kV	1	-	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	0.5kV	1	+	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	0.5kV	1	-	300ms / 5.0kHz	1 Minutes	A	
Line	1.0kV	2	+	300ms / 5.0kHz	1 Minutes	A	
Line	1.0kV	2	-	300ms / 5.0kHz	1 Minutes	A	
Neutral	1.0kV	2	+	300ms / 5.0kHz	1 Minutes	A	
Neutral	1.0kV	2	-	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	1.0kV	2	+	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	1.0kV	2	-	300ms / 5.0kHz	1 Minutes	A	
Line	2.0kV	3	+	300ms / 5.0kHz	1 Minutes	A	
Line	2.0kV	3	-	300ms / 5.0kHz	1 Minutes	A	
Neutral	2.0kV	3	+	300ms / 5.0kHz	1 Minutes	A	
Neutral	2.0kV	3	-	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	2.0kV	3	+	300ms / 5.0kHz	1 Minutes	A	
Line- Neutral	2.0kV	3	-	300ms / 5.0kHz	1 Minutes	A	

Additional Notes: A=Criteria A, B=Criteria B, C=Criteria C

NOTE:

With an aluminum electrolytic capacitor (Nippon chemi-con KY series, 470μF/50V) and a TVS (SMDJ58A, 58V, 3000Watt peak pulse power) in parallel.



10.3 Test Setup Photo




11. Surge Immunity

11.1 Test Specification and Setup

11.1.1 Test Specification

Port:	DC mains
Basic Standard:	EN 61000-4-5/ IEC 61000-4-5 (details referred to Sec 1.2)
Test Level:	Line to Line: +/- 0.5 kV, +/- 1 kV, +/- 2kV Line to Earth: +/- 0.5 kV, +/- 1 kV, +/- 2kV
Rise Time:	1.2us
Hold Time:	50us
Repetition Rate:	30 seconds
Angle:	<input type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°
Criteria:	B
Remarks:	
Test Procedure:	refer to ISL QA -T4-E-S10

11.1.2 Test Setup



11.1.3 Test Result

Performance of EUT complies with the given specification

11.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-5						Date	
EUT Model Name	THN 10-2415WIRzzzzz						2019-09-10	
Barometer Pressure	102.2kPa						Engineer	
Temperature	25°C						SAWYER	
Humidity	56%						Equipment & Test Site	
Voltage/Freq.	24 Vdc						EMC PARTNER	
							(Model:MIG0603IN3)	
A=criteria A, B=criteria B, C=criteria C								
AC Power Port:	<input type="checkbox"/>	DC Power Port:	<input checked="" type="checkbox"/>	LAN Port:	<input type="checkbox"/>	Telephone Port:	<input type="checkbox"/>	
DC Power Port								
Line Under Test	Voltage	Level	Polarity	Repetition Rate	Cycle	Pulse Position	EUT Status	Comments
Line-Neutral	0.5kV	2	+	30 sec	5		A	
Line-Neutral	0.5kV	2	-	30 sec	5		A	
Line- Neutral	1.0kV	2	+	30 sec	5		A	
Line- Neutral	1.0kV	2	-	30 sec	5		A	
Line- Neutral	2.0kV	3	+	30 sec	5		A	
Line- Neutral	2.0kV	3	-	30 sec	5		A	
Additional Notes: A=criteria A, B=criteria B, C=criteria C								
NOTE: With an aluminum electrolytic capacitor (Nippon chemi-con KY series, 470μF/50V) and a TVS (SMDJ58A, 58V, 3000Watt peak pulse power) in parallel.								



11.3 Test Setup Photo




12. Immunity to Conductive Disturbance

12.1 Test Specification and Setup

12.1.1 Test Specification

Port:	DC mains
Basic Standard:	EN 61000-4-6/ IEC 61000-4-6 (details referred to Sec 1.2)
Frequency range and Test Level: (By manufacture reference)	0.15MHz to 80MHz: 10 V
Modulation:	AM 1kHz 80%
Frequency Step:	1% of last Frequency
Dwell time:	3s
Criteria:	A
CDN Type:	CDN M2+M3
Test Procedure	refer to ISL QA -T4-E-S11

12.1.2 Test Setup



12.1.3 Test Result

Performance of EUT complies with the given specification

12.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-6	Date
EUT Model Name	THN 10-2415WIRzzzzzz	2019-09-06
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	FRANKONIA (Model: CIT-10/75)
Voltage/Freq.	24 Vdc	

A=criteria A, B=criteria B, C=criteria C

DC Power Port

Line Under Test	Frequency		Level	Modulation	Dwell time	EUT Status	Comments
	Range (MHz)	Steps %					
DC Power Port	0.15 to 80	1	10V	80% @ 1kHz	3s	A	
Additional Notes: A=criteria A, B=criteria B, C=criteria C							

12.3 Test Setup Photo




13. Power Frequency Magnetic Field immunity

13.1 Test Specification and Setup

13.1.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-8/ IEC 61000-4-8 (details referred to Sec 1.2)
Test Level:(By manufacture reference)	100A/m , continuous
Test Level:(By manufacture reference)	1000A/m , 1 sec
Polarization:	X, Y, Z
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S12

13.1.2 Test Setup



13.1.3 Test Result

Performance of EUT complies with the given specification

13.2 Test Data: Configuration 1

Basic Standard	EN 61000-4-8	Date
EUT Model Name	THN 10-2415WIRzzzzz	2019-09-06
		Engineer
Barometer Pressure	102.2kPa	SAWYER
Temperature	25°C	Equipment & Test Site
Humidity	56%	FCC(F-1000-4-8-G-125A) Immunity Loop: FCC (F-100-4-8-L-1M)
Voltage/Freq.	24 Vdc	

A=criteria A, **B=**criteria B, **C=**criteria C

Antenna Polarization	Frequency (Hz)	Test Level	Test Duration	EUT Status	Comment
X	50	100 A/m	1 Minutes	A	
Y	50	100 A/m	1 Minutes	A	
Z	50	100 A/m	1 Minutes	A	
X	50	1000 A/m	1 sec	A	
Y	50	1000 A/m	1 sec	A	
Z	50	1000 A/m	1 sec	A	

Additional Notes: A=criteria A, B=criteria B, C=criteria C

13.3 Test Setup Photo



14. Appendix

14.1 Appendix A: Test Equipment

14.1.1 Test Equipment List

Location Con03	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction 03	EMI Receiver 13	ROHDE & SCHWARZ	ESCI	101015	07/25/2019	07/25/2020
Conduction 03	LISN 15	R&S	ENV216	101335	11/22/2018	11/22/2019
Conduction 03	LISN 22	R&S	ENV216	101478	08/13/2019	08/13/2020
Conduction 03	Conduction 03 -1 Cable	WOKEN	CFD 300-NL	Conduction 03 -1	08/23/2019	08/23/2020

Location Chamber02	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Radiation (Chamber02)	BILOG Antenna 17	Schwarzbeck	Schwarzbeck VULB 9168+EMCI-N -6-05	645	03/06/2019	03/06/2020
Radiation (Chamber02)	Preamplifier 25	EMCI	EMC9135	980295	02/27/2019	02/27/2020
Radiation (Chamber02)	Coaxial Cable Chmb 02-10M-02	EMC	RG214U	Chmb 02-10M-02	08/23/2019	08/23/2020
Radiation (Chamber02)	EMI Receiver 12	ROHDE & SCHWARZ	ESCI	100804	08/14/2019	08/14/2020

Location Chmb14	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Rad. Above 1GHz	Spectrum Analyzer 25	R&S	FSV 40	101499	11/03/2018	11/03/2019
Rad. Above 1GHz	Spectrum Analyzer 24 (1G~26.5GHz)	Agilent	N9010A	MY49060537	08/29/2018	08/29/2019
Rad. Above 1GHz	Horn Antenna 06	ETS-Lindgren	3117	00066665	10/31/2018	10/31/2019
Rad. Above 1GHz	Preamplifier 13	MITEQ	JS44-0010180 0-25-10P-44	1329256	11/21/2018	11/21/2019
Rad. Above 1GHz	Microwave Cable 35	WOKEN	WCBA-WCA0 4NM.SM6	Chamber 14-1	01/31/2019	01/31/2020
Rad. Above 1GHz	Microwave Cable 36	WOKEN	WCBA-WCA0 4NM.SM0.8	Chamber 14-2	01/31/2019	01/31/2020

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
EN61K-4-2	ESD Gun 12	EM TEST	Dito	P1650188689	05/07/2019	05/07/2020
EN61K-4-3	Broadband Log-Periodic Antenna	AR	AT1080	310698	N/A	N/A
EN61K-4-3	Horn Antenna RF-01	AR	ATS700M11 G	0335864	N/A	N/A
EN61K-4-3	Amplifier 80Mz~1GHz 250W	AR	250W1000A	312494	N/A	N/A
EN61K-4-3	Amplifier 800MHz~4.2GHz 50W	AR	50S1G4M1	312762	N/A	N/A
EN61K-4-3	Amplifier 4.0~8.0GHz 35W	AR	35S4G8AM1	0335752	N/A	N/A
EN61K-4-3	Broadband Coupler 80M~1GHz	Amplifier Research	DC6180A	0341805	N/A	N/A
EN61K-4-3	Coaxial Cable	INSULATED	NPS-4806-23 60-NP3	108599.003.01.0 3	N/A	N/A
EN61K-4-3	Broadband Coupler 0.8G~4.26GHz	AR	DC7144A	0335226	N/A	N/A
EN61K-4-3	Broadband Coupler 4G~8GHz	AR	DC7350A	0335817	N/A	N/A
EN61K-4-3	Signal Generator 07	ROHDE & SCHWARZ	SMB100A	107780	10/28/2018	10/28/2019
EN61K-4-4	EFT and SURGE Test System	EM TEST	UCS-500 M6B	V0728102674	02/14/2019	02/14/2020
EN61K-4-4	Capacitive Coupling Clamp	EM TEST	HFK	0907-106	02/14/2019	02/14/2020
EN61K-4-5	CDN-UTP8 ED3	EMC-PARTNER	CDN-UTP8	1509	04/02/2019	04/02/2020
EN61K-4-5	SURGE-TESTER	EMC Partner	MIG0603IN3	523	04/02/2019	04/02/2020
EN61K-4-6	CDN M2+M3 05	Frankonia	CDN M2+M3	A2210235/2013	09/22/2018	09/22/2019
EN61K-4-6	Coaxial Cable 4-6 02-1			4-6 02-1	N/A	N/A
EN61K-4-6	Conducted Immunity Test System 02	Frankonia	CIT-10-75-D C	126B1301/2014	03/25/2019	03/25/2020
EN61K-4-6	EM-Clamp	Schaffner	KEMZ-801	19215	11/08/2018	11/08/2019
EN61K-4-8	Magnetic Field Immunity Loop	FCC	F-1000-4-8-L-1M	01037	05/27/2019	06/05/2020
EN61K-4-8	Magnetic Field Test Generator	FCC	F-1000-4-8-G -125A	01038	05/27/2019	06/05/2020

PS: N/A => The equipment does not need calibration.

****Software for Controlling Spectrum/Receiver and Calculating Test Data**

Test Item	Filename	Version
EN61000-4-2	N/A	2.0
EN61000-4-3	i2	4.130102k
EN61000-4-4	EMC TEST	4.10
EN61000-4-5	EMC TEST	4.10
EN61000-4-6	FRANKONIA CD-LAB	V5.221
EN61000-4-8	N/A	

Site	Filename	Version	Issue Date
Conduction/Radiation	EZ EMC	ISL-03A2	3/6/2013

14.2 Appendix B: Uncertainty of Measurement

The laboratory measurement uncertainty accordance with refers to CISPR 16-4-2. If U_{lab} is less than or equal to U_{cispr} in Table 1, then the test report may either state the value of U_{lab} or state that U_{lab} is less than U_{cispr} .

The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 03>

AMN: $\pm 2.90\text{dB}$

<Chamber 02 (10M)>

Horizontal

30MHz~200MHz: $\pm 4.69\text{dB}$

200MHz~1000MHz: $\pm 4.30\text{dB}$

Vertical

30MHz~200MHz: $\pm 4.65\text{dB}$

200MHz~1000MHz: $\pm 4.35\text{dB}$

<Chamber 14 (3M)>

1GHz~6GHz: $\pm 5.12\text{dB}$

<Immunity 02>

Test item	Uncertainty	Test item	Uncertainty
EN 61000-4-2 (ESD)		EN 61000-4-6 (CS)	
Rise time tr	$\leq 15\%$	CDN	$\pm 1.36\text{dB}$
Peak current Ip	$\leq 6.3\%$	EM Clamp	$\pm 3.19\text{dB}$
current at 30 ns	$\leq 6.3\%$	EN 61000-4-8 (Magnetic)	$\pm 6.55\%$
current at 60 ns	$\leq 6.3\%$		
EN 61000-4-3 (RS)	$\pm 2.19\text{dB}$		
EN 61000-4-4 (EFT)			
voltage rise time (tr)	$\pm 6.2\%$		
peak voltage value (VP)	$\pm 8.6\%$		
voltage pulse width (tw)	$\pm 5.9\%$		
EN 61000-4-5 (Surge)			
open-circuit voltage front time	$\pm 1.2\mu\text{s}$		
open-circuit voltage peak value	$\pm 8.6\%$		
open-circuit voltage duration (Td)	$\pm 50.7\mu\text{s}$		

14.3 Appendix C: Photographs of EUT

Please refer to the File of **ISL-19LE557P-1-MA**