



Characteristic Curves

TMR 4-1211


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-1212


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-1213


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-1215


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-1222


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-1223


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-2411


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-2412


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-2413


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-2415


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-2422


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-2423


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-4811


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-4812


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-4813


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-4815


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-4822


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load




Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load




Typical Input/Output Start-Up Characteristic at Full Load with Remote On




Characteristic Curves

TMR 4-4823


Efficiency versus Output Current




Efficiency versus Input Voltage




Derating Output versus Ambient Temperature




Typical Output Ripple and Noise at Full Load



Transient Response to Dynamic Load Change (25%)



Typical Input/Output Start-Up Characteristic at Full Load



Typical Input/Output Start-Up Characteristic at Full Load with Remote On

