



Characteristic Curves

TEL 10-2410WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-2411WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-2412WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-2413WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-2415WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-2422WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-2423WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-4810WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




TEL 10-4811WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-4812WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-4813WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-4815WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-4822WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 10-4823WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature



Typical Start-Up and Output Rise Characteristic



Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)

