

TRACOPower

Model: TPC 080-124

EMC – Test Report

EUT: TRACOPower Model: TPC 080-124

Serial No.: 31206570468_Winsdon Sample

Manufacturer No.: 080PSC184

Manufacturer: Convertec Ltd.
Whitemill Industrial Estate
Wexford
Republic of Ireland

Tester: Kevin Burke, Convertec

Date: 8/3/2012

It should be noted, that combining two or more CE compliant finished appliances does not automatically produce a compliant system. The manufacturer of an apparatus or a fixed installation as defined in the “Guide for the EMC Directive 2004/108EC, 21. May 2007” is responsible for the EMC-compliance of the final apparatus.

Table of Contents:

| | |
|--|----|
| <u>1</u> Conducted Input Emissions Test | 3 |
| <u>1.1</u> Test Setup..... | 3 |
| <u>1.2</u> Conducted Input Emissions Results..... | 4 |
| <u>2</u> Conducted Output Emissions Test | 5 |
| <u>3</u> Radiated Emissions Test..... | 6 |
| <u>3.1</u> Test Setup..... | 7 |
| <u>3.2</u> Radiated Emissions Results..... | 8 |
| <u>4</u> Harmonic Current Emissions Test | 9 |
| <u>4.1</u> Test Setup:..... | 9 |
| <u>4.2</u> Harmonic Current Emissions Test Results:..... | 10 |
| <u>5</u> Electrostatic Discharge Test..... | 11 |
| <u>5.1</u> Test Set-Up: | 11 |
| <u>5.2</u> Electrostatic Discharge Test Results..... | 12 |
| <u>6</u> Surge Test | 13 |
| <u>6.1</u> Test Setup..... | 13 |
| <u>6.2</u> Surge Results..... | 14 |
| <u>7</u> Fast Transient Test (Burst) | 15 |
| <u>7.1</u> Test Setup..... | 15 |
| <u>7.2</u> Fast Transient Test (Burst) Test Results..... | 16 |
| <u>6</u> Voltage Dips and Short Interruptions Test | 17 |
| <u>6.1</u> Test Setup..... | 18 |
| <u>6.2</u> Voltage Dips & Short Interruptions Results (Classifications)..... | 18 |
| <u>7</u> Conducted Input RF Immunity Test..... | 20 |
| <u>9.1</u> Test Setup..... | 20 |
| <u>9.2</u> Conducted Input RF Immunity Results..... | 21 |
| <u>8</u> Conducted Output RF Immunity Test | 22 |
| <u>10.1</u> Test Setup:..... | 22 |
| <u>10.2</u> Conducted Output RF Immunity Results..... | 23 |
| <u>9</u> Radiated RF Immunity Test..... | 24 |
| <u>11.1</u> Test Setup..... | 24 |
| <u>11.2</u> Radiated RF Immunity Results..... | 25 |
| <u>12</u> Power Frequency Magnetic Field Immunity Test..... | 26 |
| <u>12.1</u> Test Setup..... | 26 |
| <u>12.2</u> Power Frequency Magnetic Field Immunity Results..... | 27 |
| <u>13</u> Semi F47 Test..... | 28 |
| <u>13.1</u> Test Setup..... | 28 |
| <u>13.2</u> SEMI F47 Results..... | 29 |
| <u>14</u> Summary..... | 30 |
| <u>15</u> List of Equipment Used:..... | 32 |

1 Conducted Input Emissions Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standards: IEC61000-6-3: 2006 referring to CISPR 16-1-2: 2003

Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive).
- Emissions measured using Agilent E7402A EMC Analyzer and PMM LISN L2-16
- Tested to CISPR 16 -1-2:2003 Class B limits
- Transient limiter used to protect Agilent E7402A, with appropriate correction factors applied
- Tests carried out in a shielded room

1.1 Test Setup

Test Equipment Settings:


| Start Freq. | Stop Freq. | Pk Time | Qpk Time | Avg Time |
|-------------|------------|---------|----------|----------|
| 150kHz | 30MHz | 200ms | 200ms | 200ms |

Test Setup:




1.2 Conducted Input Emissions Results

L1



L2



Remarks:

The blue and green lines represent peak measurements. Quasi peak and average measurements are measured if the peak measurement is above the relevant limit. Not needed in this case.

PASS

2 Conducted Output Emissions Test

Not needed for the TPC range.

3 Radiated Emissions Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standards: IEC61000-6-3: 2006 referring to CISPR 16-2-3:2003

For an apparatus to comply with EMC radiated emissions requirements as set down in CISPR 16-2-3, free field measurements need to be performed. A test method similar to that described in IEC61204-3 (for low-voltage power supplies) section 6.4.2 shall be used here instead of free field measurements. This test is designed to give a good indication of whether an EUT will pass free field measurements or not. The absorber clamp used in this method is replaced by a Fischer high frequency current probe (Model: F-33-1). The limits used are set by comparison with open field measurements and are compensated by 20dB per frequency decade. Two limit lines are indicated; Fis_a and Fis_b, and the results may be interpreted as follows:

- Below limit line Fis_b: Limits are kept
- Below limit line Fis_a: Limits probably kept
- Above limit line Fis_a: Limits most likely not kept

Final Compliance can only be established by free field measurements in accordance to the relevant standard applicable to the apparatus or enclosure in which the power supply is used

Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive).
- Emissions measured using receiver Agilent E7402A and FCC RF current probe
- RF current probe kept a distance of 10cm from input/output
- Tests carried out in shielded room
- Tested to CISPR 16 -2-3:2003 Class B limits

3.1 Test Setup




Figure 1. Test set-up for measurement of disturbance power similar to IEC61204-3

Test Equipment Settings:


| Start Freq. | Stop Freq. | Pk Time |
|-------------|------------|---------|
| 30MHz | 300MHz | 200ms |

Test Setup: The following shows the setup used for input lines, the setup used for the output lines is the same with the clamp on the output lines.




3.2 Radiated Emissions Results

Input Lines:



Output Lines:



PASS


4 Harmonic Current Emissions Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-3: 2006 referring to IEC 61000-3-2: 2005


Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive)
- EUT powered by low-distortion AC Voltage Source, TTI AC-1000
- Harmonic Limits measured using LMG 95 Power Meter
- Tested to IEC61000-3-2 Table 1 Class A

4.1 Test Setup:



4.2 Harmonic Current Emissions Test Results:



| Harmonic | Current (A) | Limit (A) | Harmonic | Current (A) | Limit (A) |
|----------|-------------|-----------|----------|-------------|-----------|
| 0 | 0.0009 | | 20 | 0.0003 | 0.0920 |
| 1 | 0.4088 | | 21 | 0.0550 | 0.1071 |
| 2 | 0.0009 | 1.0800 | 22 | 0.0003 | 0.0836 |
| 3 | 0.3835 | 2.3000 | 23 | 0.0539 | 0.0978 |
| 4 | 0.0009 | 0.4300 | 24 | 0.0003 | 0.0767 |
| 5 | 0.3559 | 1.1400 | 25 | 0.0532 | 0.0900 |
| 6 | 0.0008 | 0.3000 | 26 | 0.0002 | 0.0708 |
| 7 | 0.3172 | 0.7700 | 27 | 0.0495 | 0.0833 |
| 8 | 0.0007 | 0.2300 | 28 | 0.0002 | 0.0657 |
| 9 | 0.2707 | 0.4000 | 29 | 0.0426 | 0.0776 |
| 10 | 0.0006 | 0.1840 | 30 | 0.0002 | 0.0613 |
| 11 | 0.2205 | 0.3300 | 31 | 0.0339 | 0.0726 |
| 12 | 0.0005 | 0.1533 | 32 | 0.0002 | 0.0575 |
| 13 | 0.1706 | 0.2100 | 33 | 0.0255 | 0.0682 |
| 14 | 0.0004 | 0.1314 | 34 | 0.0002 | 0.0541 |
| 15 | 0.1250 | 0.1500 | 35 | 0.0199 | 0.0643 |
| 16 | 0.0004 | 0.1150 | 36 | 0.0002 | 0.0511 |
| 17 | 0.0882 | 0.1324 | 37 | 0.0183 | 0.0608 |
| 18 | 0.0004 | 0.1022 | 38 | 0.0002 | 0.0484 |
| 19 | 0.0644 | 0.1184 | 39 | 0.0188 | 0.0577 |

PASS


5 Electrostatic Discharge Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2: 2005 referring to IEC 61000-4-2: 2000

Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive)
- Since the EUT output is isolated from earth, a 470K HV resistor was placed between output and Earth to provide a discharge path between spikes
- Contact discharge tests shall be applied to all areas exposed to the end user under final installation using ESD gun SEDS 200
- Test voltage shall be increased from 2kV up to the max 8kV/4kV (air/contact) as required by the standard IEC/EN 61000-4-2
- At least 10 discharges were applied per test-point (in both polarities)
- A time interval between discharges of a least 1s was used
- The ESD generator was held perpendicular to the test-point wherever possible for repeatability of results
- In the case of contact discharges, the trigger is engaged at about 20cm and the tester is moved quickly toward the testpoint until a spark occurs and trigger is released

5.1 Test Set-Up:



5.2 Electrostatic Discharge Test Results

All exposed metal screw heads and connector pins and ground planes were tested as contact testpoints and also as air testpoints.

The plastic case and all vents and inlets were also tested as air testpoints.

| | Contact Testpoints: | Air Testpoints: |
|-----|---------------------|-----------------|
| EUT | PASS | PASS |

Conclusion:

EUT still functions as expected after tests therefore are in accordance with IEC61000-4-2

PASS


6 Surge Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2: 2005 referring to IEC 61000-4-5: 2005

Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.3A Resistive)
- Used Haefely Surge generator PSURGE 4010
- Voltage test level: +/- 1kV Line-Line, +/- 2kV Line-Earth (installation class 3)
- No. of Surges per set: 5 tests Positive and 5 tests Negative
- Interval Between Surges: 10s

6.1 Test Setup



6.2 Surge Results

| | L+VE to L-VE | L+VE to PE | L-VE to PE |
|----------------|--------------|------------|------------|
| EUT: 080PSC184 | PASS | PASS | PASS |

Conclusion:

Meets Classification B as required per Table 6, IEC 61204-3

PASS

7 Fast Transient Test (Burst)

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2: 2005 referring to IEC 61000-4-4: 2004

Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive)
- Units tested to IEC61000-4-4 test level 3
- Used Haefely Burst tester PEFT 4010
- Voltage test level: +/-2Kv
- Burst Duration: 0.75ms
- Repition rate: 100kHz
- Burst Period: 300ms
- Individual test time: 1 min
- Polarity: Positive and Negative

The output lines were also tested as above to +/-1kV with Haefely coupling capacitor IP4A

7.1 Test Setup



7.2 Fast Transient Test (Burst) Test Results.

| EUT: 080PSC184 | +VE-G | -VE-G | PE-G | +VE, -VE-G | +VE,PE-G | -VE,PE-G | +VE, -VE,PE-G Outputs -G |
|----------------|-------|-------|------|------------|----------|----------|--------------------------|
| Positive | PASS | PASS | PASS | PASS | PASS | PASS | PASS PASS |
| Negative | PASS | PASS | PASS | PASS | PASS | PASS | PASS PASS |

Conclusion:

Meets Classification B as required per Table 6, IEC 61204-3

PASS


6 Voltage Dips and Short Interruptions Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2:2005 referring to IEC 61000-4-11:2004

Notes:

- EUT tested at full load (24V/3.33A Resistive)
- Test carried out using 2 Variacs and dropout simulator NSG 1003
- Tested according to class 3 IEC61000-4-11 (as per Annex B)
- Unit tested with the highest nominal and lowest nominal voltage (240V/110V) in accordance with IEC61000-4-11 section 5
- Interval between dropouts and short interruptions was 10s
- Phase angle was set to 0°, 90°, 180°, 270° for each voltage level tested
- Voltage Dips were tested from 100%-80% for 250 Mains cycles in accordance with IEC61000-4-11 table 2
- Voltage Dips were tested from 100%-70% for 25 Mains cycles in accordance with IEC61000-4-11 table 2
- Voltage Dips were tested from 100%-40% for 10 Mains cycles in accordance with IEC61000-4-11 table 2
- Voltage Dips were tested from 100%-0% for 1 Mains cycle in accordance with IEC61000-4-11 table 2
- 3 Voltage dips and 3 Short Interruptions were carried out per test
- Short interruptions tests were carried out at 100% to 0% for each duration 0.1s, 0.2s, 0.5s, 1s, 2s, and 5s.
- Short interruptions were done at worst case 0° phase angle
- Classification of performance in accordance to IEC61000-4-1 Section 9.

1.1 Test Setup



8.2 Voltage Dips & Short Interruptions Results (Classifications)

Voltage Dips

| 240VAC | | | | |
|--------------|---|----|-----|-----|
| Phase Angle: | 0 | 90 | 180 | 270 |
| 100%-0% | A | A | A | A |
| 100%-40% | B | B | B | B |
| 100%-70% | A | A | A | A |
| 100%-80% | A | A | A | A |

| 110VAC | | | | |
|--------------|---|----|-----|-----|
| Phase Angle: | 0 | 90 | 180 | 270 |
| 100%-0% | B | B | B | B |
| 100%-40% | B | B | B | B |
| 100%-70% | B | B | B | B |
| 100%-80% | B | B | B | B |

Short Interruptions

| 100%-0% | 0.1s | 0.2s | 0.5s | 1s | 2s | 5s |
|---------|------|------|------|----|----|----|
| 110VAC | B | B | B | B | B | B |
| 240VAC | B | B | B | B | B | B |

Conclusion:

Test Result were evaluated in relation to the Customer Specification CS-030/050/080/120/PSC.doc and the UUT was considered to have PASSED the tests.

PASS

7 Conducted Input RF Immunity Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2: 2005 referring to IEC 61000-4-6:2004

Notes:


- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive)
- Test carried out using test generator “EM Test CWS 500N”, Coupling/Decoupling network “EM Test CDN M2/M3”, an attenuator “EM Test ATT6/75” and measurement instrument “Agilent 34410A”
- Unit tested to IEC61000-4-6 test level 3

9.1 Test Setup


Test Equipment Settings:

| Frq. start [MHz] | Level start [V] | Frq. stop [MHz] | Level stop [V] | Frq. step | td [s] | tp [s] | Modulation |
|------------------|-----------------|-----------------|----------------|-----------|--------|--------|-------------|
| 0.150 | 10.0 | 80.000 | 10.0 | 1.0 % | 0.5 | 0.0 | AM 1kHz 80% |

Test Setup:



9.2 Conducted Input RF Immunity Results



Conclusion:

Meets Classification A (Ref. Section 9, IEC 61000-4-3)

Test Results were evaluated in relation to the Customer Specification

CS-030/050/080/120/PSC.doc and the output did not change by more than +/-120mV therefore UUT was considered to have PASSED the tests.

PASS

8 Conducted Output RF Immunity Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2: 2005 referring to IEC 61000-4-6:2004

Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive)
- Test carried out using test generator “EM Test CWS 500N”, Coupling/Decoupling network “EM Test CDN M2/M3”, an attenuator “EM Test ATT6/75”, measurement instrument “Agilent 34410A” and FCC-801-M2-50A Coupling/Decoupling network.
- Unit tested to IEC61000-4-6 test level 3

10.1 Test Setup:


Test Equipment Settings:

| Frq. start [MHz] | Level start [V] | Frq. stop [MHz] | Level stop [V] | Frq. step | td [s] | tp [s] | Modulation |
|------------------|-----------------|-----------------|----------------|-----------|--------|--------|-------------|
| 0.150 | 10.0 | 80.000 | 10.0 | 1.0 % | 0.5 | 0.0 | AM 1kHz 80% |

Test Setup:



10.2 Conducted Output RF Immunity Results



Conclusion:

Meets Classification A (Ref. Section 9, IEC 61000-4-3)

Test Results were evaluated in relation to the Customer Specification

CS-030/050/080/120/PSC.doc and the output did not change by more than +/-120mV therefore UUT was considered to have PASSED the tests.

PASS

9 Radiated RF Immunity Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2: 2005 referring to IEC61000-4-3: 2004

Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive)
- Test carried out using test generator “EM Test CWS 500N”, E-field probe and measurement instrument “Agilent 34410A”

11.1 Test Setup

Test Equipment Settings:

| Frq. start [MHz] | Level start [V] | Frq. stop [MHz] | Level stop [V] | Frq. step | td [s] |
|------------------|-----------------|-----------------|----------------|-----------|--------|
| 80.0 | 20.0 | 1000.0 | 20.0 | 1.0 % | 1 |

Test Setup:



11.2 Radiated RF Immunity Results

Conclusion:

Meets Classification A (Ref. Section 9, IEC 61000-4-3)

Test Results were evaluated in relation to the Customer Specification

CS-030/050/080/120/PSC.doc and the UUT was considered to have PASSED the tests.

PASS

12 Power Frequency Magnetic Field Immunity Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: IEC61000-6-2: 2005 referring to IEC61000-4-8: 2001


Notes:

- EUT tested under normal operating conditions of 230V 50Hz input at full load (24V/3.33A Resistive)
- Test carried out using test generator “Chroma Programmable AC Source”, “1meter x 1meter 100 turn Induction Coil” and measurement instrument “Agilent 34405A”
- Unit tested to IEC61000-4-8 test levels 5



12.1 Test Setup

Test Equipment Settings:

| Test generator settings | | | |
|-------------------------|--|-------------------------------|----------------------------|
| Frequency | AC Current through Induction Coil (Arms) | Magnetic Field Strength (A/m) | Applied Field duration [s] |
| 50Hz | 1 | 100 | Continuous |
| 60Hz | 1 | 100 | Continuous |
| 50Hz | 10 | 1000 | 3 |
| 60Hz | 10 | 1000 | 3 |



12.2 Power Frequency Magnetic Field Immunity Results



Conclusion:

Meets Classification A (Ref. Section 9, IEC 61000-4-8)

Test Results were evaluated in relation to the Customer Specification

CS-030/050/080/120/PSC.doc and the UUT was considered to have PASSED the tests.

PASS


13 Semi F47 Test

Equipment Under Test: TPC 080-124
EUT Serial No.: 31206570468
Customer Spec: CS-030/050/080/120/PSC.doc
Date: 8/3/2012
Standard: SEMI F47-0706

Notes:

- EUT tested under operating conditions of 230V/110V 50Hz input at full load (24V/3.33A Resistive)
- Test carried out using test generator using Voltage Sag Generator: Schaffner NSG1003: Dropout and Variation Simulator and Oscilloscope Tektronix: TDS220


13.1 Test Setup



13.2 SEMI F47 Results


Input Voltage VAC = 230V, Output = 24VDC, 3.33A

| Voltage Sag | Duration | Duration | Output Voltage | Percent delta of Nominal | SEMIF47 [%] | Result |
|-------------|----------|----------|----------------|--------------------------|-------------|--------|
| [V] | [s] | cycles | [V] | DUT 50Hz [%] | | |
| 207 | 20 | 1000 | 24.0 | 0.0 | 90 | PASS |
| 207 | 10 | 500 | 24.0 | 0.0 | 90 | PASS |
| 184 | 10 | 500 | 24.0 | 0.0 | 80 | PASS |
| 184 | 1 | 50 | 24.0 | 0.0 | 80 | PASS |
| 184 | 0.5 | 25 | 24.0 | 0.0 | 80 | PASS |
| 161 | 0.5 | 25 | 24.0 | 0.0 | 70 | PASS |
| 161 | 0.5 | 10 | 24.0 | 0.0 | 70 | PASS |
| 115 | 0.2 | 10 | 24.0 | 0.0 | 50 | PASS |
| 115 | 0.02 | 1 | 24.0 | 0.0 | 50 | PASS |
| 0 | 0.02 | 1 | 24.0 | 0.0 | 0 | PASS |



Input Voltage VAC = 110V, Output = 24VDC, 3.33A

| Voltage Sag | Duration | Duration | Output Voltage | Percent delta of Nominal | | |
|-------------|----------|----------|----------------|--------------------------|--------------|--------|
| [V] | [s] | cycles | [V] | DUT 50Hz [%] | SEMI F47 [%] | Result |
| 99 | 20 | 1000 | 24.0 | 0.0 | 90 | PASS |
| 99 | 10 | 500 | 24.0 | 0.0 | 90 | PASS |
| 88 | 10 | 500 | 22.2 | 7.5 | 80 | PASS |
| 88 | 1 | 50 | 22.2 | 7.5 | 80 | PASS |
| 88 | 0.5 | 25 | 22.2 | 7.5 | 80 | PASS |
| 77 | 0.5 | 25 | 19.8 | 17.5 | 70 | PASS |
| 77 | 0.2 | 10 | 19.8 | 17.5 | 70 | PASS |
| 55 | 0.2 | 10 | 16.0 | 33.3 | 50 | PASS |
| 55 | 0.02 | 1 | 19.6 | 18.3 | 50 | PASS |
| 0 | 0.02 | 1 | 18.4 | 23.3 | 0 | PASS |



Conclusion:

Meets Classification B (Ref. SEMI F47-0706)

Test Results were evaluated in relation to the Customer Specification CS-030/050/080/120/PSC.doc and the UUT was considered to have PASSED the tests.

PASS

14 Summary

| Regulation | Class/Test Level | Result | Comments |
|------------|------------------|--------|----------|
|------------|------------------|--------|----------|

| | | | |
|---|-------------------------------------|------|--|
| IEC61000-6-3: 2006 + CISPR 16-1-2: 2003 + CISPR 16-2-3: 2003 | | | |
| Conducted Input (0.15-30MHz) | Class B | PASS | |
| Conducted Output (0.15-30MHz) | Class B | N/A | |
| Radiated (30-300MHz) | Class B | PASS | |
| IEC61000-6-2: 2005 + IEC 61000-4-2:2005 | | | |
| Electrostatic Discharge | | | |
| - Air Discharge | +/- 2/8kV (Class B) | PASS | |
| - Contact Discharge | +/- 2/4kV (Class B) | PASS | |
| IEC61000-6-2: 2005 + IEC 61000-4-5:2005 | | | |
| Surge | | | |
| - AC Supply | +/- 1kV (Class B) +VE to -VE | PASS | |
| | +/- 2kV (Class B) +VE to PE | PASS | |
| | +/- 2kV (Class B) -VE to PE | PASS | |
| IEC61000-6-2: 2005 + IEC 61000-4-4: 2004 | | | |
| Fast Transient (Burst) | | | |
| - AC Supply | +/- 2kV (Class B) between all lines | PASS | |
| - Outputs | +/- 1kV (Class B) between all lines | PASS | |
| IEC61000-6-2: 2005 + IEC61000-4-6:2004 | | | |
| Conducted Input RF Immunity | Level III 10V (Class A) | PASS | |
| Conducted Output RF Immunity | Level III 10V (Class A) | PASS | |
| IEC61000-6-2: 2005 + IEC61000-4-3:2004 | | | |
| Radiated RF Immunity | 20V (Class A) | PASS | |
| IEC61000-6-2: 2005 + IEC61000-4-8: 2001 | | | |
| Power Frequency Magnetic Field Immunity | Level 5 (Class A) | PASS | |
| IEC61000-6-2:2005 + IEC 61000-4-11:2004 | | | |
| Voltage Dips | | | |
| -AC Supply (240VAC and 110VAC) | 100%-0% (Class B) | PASS | |
| | 100%-40% (Class B) | PASS | |
| | 100%-70% (Class B) | PASS | |

| | | | |
|--|--------------------|------|--|
| | 100%-80% (Class B) | PASS | |
| Short Interruptions (100%-0% for: 0.1s, 0.2s, 0.5s, 1s, 2s and 5s) | 100%-0% (Class B) | PASS | |
| SEMI F47-0706 | | | |
| Semi F47 Voltage SAG Immunity | | | |
| -AC Supply (230VAC and 110VAC) | (Class B) | PASS | |

15 List of Equipment Used:

| Description | Model No. | Manufacturer | Serial No. |
|------------------|----------------|--------------|------------|
| EMC Analyzer | E7402A | Agilent | MY45119210 |
| LISN 1 | PMM L2-16 | PMM | 1230L00301 |
| LISN 2 | FCC-801-M2-50A | FCC | 3035 |
| RF Current Probe | F-33-1 | FCC | 759 |

| | | | |
|-----------------------------|-------------|-----------------|-----------------|
| Transient Limiter | 11947A | Agilent | 3107A03645 |
| Precision Power Meter | LMG95 | Zimmer | 10790709 |
| ESD Gun | SESD 200 | Schloder | 142261 |
| Surge Generator | PSURGE 4010 | Haefely | 583 334-63 |
| Burst generator | PEFT 4010 | Haefely | 080 981-08 |
| Coupling Capacitor | IP4A | Haefely | 171241 |
| Electronic Load | ELA 500 | Zentro-Electrik | 63145803 |
| High Power Resistors | n/a | n/a | n/a |
| Multimeter | 34405A | Agilent | TW46290007 |
| Multimeter | 34405A | Agilent | TW46290015 |
| Multimeter | 34410A | Agilent | MY47012359 |
| Multimeter | 1906 | TTI | n/a |
| High frequency generator | CWS 500N | EM Test | V0847104427 |
| Coupling/Decoupling Network | CDN M2/M3 | EM Test | 1108-34 |
| Attenuator | ATT6/75 | EM Test | 1107-53 |
| Oscilloscope | TDS1002 | Tektronix | C016388 |
| Programmable AC Source | 61604 | Chroma | ABR000000672 |
| Cables | Type | Length | Comments |
| Mains Supply Cable | 3-wire | 1m | Unshielded |
| DC Lines Cable | 2-wire | 1m | Unshielded |