

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product

Switching power supply

Name and address of the applicant

TRACO ELECTRONIC AG
SIHLBRUGGSTRASSE 111, CH-6340 BAAR, SWITZERLAND

Name and address of the manufacturer

TRACO ELECTRONIC AG
SIHLBRUGGSTRASSE 111, CH-6340 BAAR, SWITZERLAND

Name and address of the factory

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)

TRACO or



Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

TPP 40-1(V)Eed-B1zzzzzzzz, TPP 40-1(V)EedB1zzzzzzzz, TPP 40-1(V)Eedzzzzzzzz, TPP 40-1(V)Xbzzzzzzzz, TPP 40-1L(V)Xbzzzzzzzz, TPP 40-2(V1)(V2)(XX)Xbzzzzzzzz, See Page 2

Additional information (if necessary may also be reported on page 2)

National Differences specified in the CB Test Report.
Additionally evaluated to EN 60601-1:2006/ A1:2013/ A12:2014
☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60601-1:2005/AMD1:2012, IEC 60601-1:2005

As shown in the Test Report Ref. No. which forms part of this Certificate

200704401 issued on 2021-01-07

This CB Test Certificate is issued by the National Certification Body

UL (US), 333 Pfingsten Rd L 60062, Northbrook, USA
UL (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK
UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

Date: 2021-01-12

Signature:

Jan-Erik StorgaardFor full legal entity names see www.ul.com/ncbnames

Model Details:

TPP 40-1L(V)Xbzzzzzzzz, TPP 40-1(V)Xbzzzzzzzz, TPP 65-1L(V)Xbzzzzzzzz, TPP 65-1(V)Xbzzzzzzzz,
(where X can be A or U or D or blank;
L for low efficiency or blank for standard,
(V) can be 05, 07, 09, 12, 15, 18, 24, 28, 36, 48 or 53; b can be -J, J or blank;
z can be any alphanumeric or dash or blank for marketing purpose and no impact safety related critical components and constructions.)
TPP 40-1(V)EedB1zzzzzzzz, TPP 65-1(V)EedB1zzzzzzzz, TPP 40-1(V)Eed-B1zzzzzzzz, TPP
65-1(V)Eed-B1zzzzzzzz, TPP 40-1(V)Eedzzzzzzzz, TPP 65-1(V)Eedzzzzzzzz,
(where e can be -J, -D, -M, -T or J, D, M, T or blank;
B1 or -B1 for low efficiency or blank for standard,
(V) can be 05, 07, 09, 12, 15, 18, 24, 28, 36, 48 or 53;
d can be -D1, D1 or blank;
z can be any alphanumeric or dash or blank for marketing purpose and no impact safety related critical components and constructions.)
TPP 40-2(V1)(V2)(XX)Xbzzzzzzzz, TPP 65-2(V1)(V2)(XX)Xbzzzzzzzz,
(where X can be A or U or D or blank;
(V1) can be any number between 1 to 5 or V7.5 or V9 or V28;
(V2) can be any number between 0 to 3 or X;
(XX) can be any number between V1.0 and V15 designating the output voltage or blank;
b can be -J, J or blank;
z can be any alphanumeric or dash or blank for marketing purpose and no impact safety related critical components and constructions.)
TPP 40-3(V1)(V2)(XX)(V3)(YY)Xbzzzzzzzz, TPP 65-3(V1)(V2)(XX)(V3)(YY)Xbzzzzzzzz, TPP
40-3(V1)(V2)(XX)M(V3)(YY)Xbzzzzzzzz, TPP 65-3(V1)(V2)(XX)M(V3)(YY)Xbzzzzzzzz,
(where X can be A or U or D or blank;
(V1) can be any number between 1 to 5 or V7.5 or V9 or V28;
(V2) can be any number between 0 to 3 or X;
(V3) can be any number between 0 to 5 or Y;
(XX) can be any number between V1.0 and V15 designating the output voltage or blank;
(YY) can be any number between V1.0 and V24 designating the output voltage or blank;
b can be -J, J or blank;
z can be any alphanumeric or dash or blank for marketing purpose and no impact safety related critical components and constructions.)

Ratings:

Input: 100-240 V a.c., 50/60 Hz,

1.0-0.5 A for TPP 40-1L(V)Xzzzzzzzz, TPP 40-1(V)Xbzzzzzzzz, TPP 40-1(V)EedB1zzzzzzzz, TPP
40-1(V)Eed-B1zzzzzzzz, TPP 40-1(V)Eedzzzzzzzz;

1.6-0.9 A for TPP 65-1L(V)Xbzzzzzzzz, TPP 65-1(V)Xbzzzzzzzz, TPP 65-1(V)EedB1zzzzzzzz, TPP
65-1(V)Eedzzzzzzzz;

1.05-0.55 A for TPP 40-2(V1)(V2)(XX)Xbzzzzzzzz, TPP 40-3(V1)(V2)(XX)M(V3)(YY)Xbzzzzzzzz and TPP
40-3(V1)(V2)(XX)M(V3)(YY)Xbzzzzzzzz;

1.65-0.95 A for TPP 65-2(V1)(V2)(XX)Xbzzzzzzzz, TPP 65-3(V1)(V2)(XX)(V3)(YY)Xbzzzzzzzz and TPP
65-3(V1)(V2)(XX)M(V3)(YY)Xbzzzzzzzz

Output Rating:

See "General product information" in Test Report for details.

Additional Information:

The risk management requirements of the standard were not addressed.

Additional information (if necessary)



UL (US) 333 Pfingsten Rd L 60062 Northbrook USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA) 7 Underwriters Road Toronto M1R 3B4 Ontario CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2021-01-12

Signature:

Jan-Erik Storgaard