



Certificate Number: 0326192-9

Date: 2019-05-24

UL CONDITIONS OF ACCEPTABILITY

Company Name: TRACO ELECTRONIC AG

File-CCN: E188913 – QQJQ2 & QQJQ8

Product Description: DC to DC Converter

Models: TMDC 06-7211H-B1, TMDC 06-7211H, TMDC 06-7212H, TMDC 06-7213H, TMDC 06-7215H, TMDC 06-7218H, TMDC 06-7222H, TMDC 06-7223H, TMDC 06-7225H

Conditions Of Acceptability:

For use only in or with complete equipment where the acceptability of the combination is determined by UL LLC. When installed in an end-product, consideration must be given to the following:

- The equipment is suitable for direct connection after isolated secondary circuitry.
- The outputs of this component DC/DC converter have been evaluated for PS3 and ES1; the ES classification of circuits and parts that are accessible to ordinary persons should be reconsidered when it's employed in the end-use equipment.
- The metal base plate was investigated as part of the protective earthing/bonding and shall be evaluated in end use product.
- The terminals of this component DC/DC converter are only suitable for factory wiring only.
- Electrical Energy Source of unit output (V+ to earth, GND to earth) under normal, abnormal operation and single fault condition should be considered in the end product investigation.
- The rated input range for all models is 80-160 Vdc. Tests were done, assuming the insulation is reinforced for working voltage 1000 Vrms. Reinforced insulation between input and output is assured by potting of the device. Thermal cycling procedure performed. Only distance through solid insulation exists. The product is considered providing reinforced insulation between input and output up, a maximum potential of 1000 Vrms / 1410 Vpeak.

The equipment has been evaluated for reinforced Insulation and intended to be supplied by an isolated or non-isolated DC source; the transient voltage through the DC source is assuming up to 2500Vpk maximum.

- The need for suitable Electrical enclosure (for ES safeguard), fire enclosure (for PS safeguard), mechanical enclosure (for MS safeguard), and safeguard for thermal burn injury (for TS safeguard) is to be evaluated and provided (if necessary) when it's employed in the end-use equipment.
- The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation system with the indicated rating greater than Class A (105°C): T1 (Class B).

Ratings:

All models are similar except for ratings, PCB layout, schematic, windings of transformer and model designation, see below.

Model No.	Input Voltage Range	Rated Input Current (max mA)	Output Voltage (Vdc)	Output Current (mA)
TMDC 06-7211H-B1	Nominal: 110Vdc Range: 80-160Vdc	101	5.0	1200
TMDC 06-7211H			5.1	1200
TMDC 06-7212H			12.0	500
TMDC 06-7213H			15.0	400
TMDC 06-7215H			24.0	250
TMDC 06-7218H			48.0	125
TMDC 06-7222H			±12.0	±250
TMDC 06-7223H			±15.0	±200
TMDC 06-7225H			±24.0	±125

Nomenclature: N/A