



### Characteristic Curves

#### TXLN 750-112


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output Load versus Input Voltage




Typical Output Ripple and Noise at 115 Vin (with external capacitor; see datasheet)




Typical Output Ripple and Noise at 230 Vin (with external capacitor; see datasheet)



Transient Response to Dynamic Load Change (25%) at 115 Vin




Transient Response to Dynamic Load Change (25%) at 230 Vin






### TXLN 750-124


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output Load versus Input Voltage




Typical Output Ripple and Noise at 115 Vin (with external capacitor; see datasheet)




Typical Output Ripple and Noise at 230 Vin (with external capacitor; see datasheet)



Transient Response to Dynamic Load Change (25%) at 115 Vin




Transient Response to Dynamic Load Change (25%) at 230 Vin




### TXLN 750-124


#### Typical Start-Up Characteristic at 115 Vin




#### Typical Start-Up Characteristic at 230 Vin




#### Typical Output Rise Characteristic at 115 Vin




#### Typical Output Rise Characteristic at 230 Vin



#### Typical Hold-Up Characteristic at 115 Vin




#### Typical Hold-Up Characteristic at 230 Vin




### TXLN 750-148


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output Load versus Input Voltage




Typical Output Ripple and Noise at 115 Vin  
(with external capacitor; see datasheet)



Typical Output Ripple and Noise at 230 Vin  
(with external capacitor; see datasheet)



Transient Response to Dynamic Load Change (25%)  
at 115 Vin



Transient Response to Dynamic Load Change (25%)  
at 230 Vin

