



Characteristic Curves

TEN 60-2411WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-2411WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-2412WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-2412WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-2413WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-2413WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-2415WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-2415WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-2422WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-2422WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-2423WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-2423WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-2425WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-2425WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-4811WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-4811WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-4812WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-4812WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-4813WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-4813WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-4815WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-4815WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-4822WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-4822WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-4823WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-4823WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)




Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic




Remote on/off Voltage Start-Up Characteristic




TEN 60-4825WIN


Efficiency vs Output Load




Power Dissipation versus Output Load




Efficiency vs Input Voltage




Derating Output Load versus Ambient Temperature



Derating Output Load versus Ambient Temperature with Heatsink




Derating Output Load versus Ambient Temperature with Heatsink (-HS1 / -HS8 / -HS9 / -HS10)




TEN 60-4825WIN


Typical Output Ripple and Noise
(with external capacitor; see datasheet)



Transient Response to Dynamic Load Change (25%)



Typical Input Start-Up and Output Rise Characteristic



Remote on/off Voltage Start-Up Characteristic

