



### Characteristic Curves

#### TPP 65-105A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




### TPP 65-105A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

### TPP 65-112A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

### TPP 65-112A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

### Optional model with 15 Vout


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

### Optional model with 15 Vout


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin




Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

### TPP 65-124A


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Derating Output versus Input Voltage




Typical Output Ripple and Noise at 115 Vin




Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin



Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.




### TPP 65-124A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin




Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin





Typical Hold-Up Characteristic at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.




### Efficiency versus Output Load




### Derating Output Load versus Ambient Temperature




### Derating Output versus Input Voltage




### Typical Output Ripple and Noise at 115 Vin




### Typical Output Ripple and Noise at 230 Vin



Transiente Response (25% load step) at 115 Vin




Transiente Response (25% load step) at 230 Vin




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

### TPP 65-148A


Typical Input Start-Up Characteristic at 115 Vin




Typical Input Start-Up Characteristic at 230 Vin




Typical Output Rise Characteristic at 115 Vin



Typical Output Rise Characteristic at 230 Vin



Typical Hold-Up Characteristic at 115 Vin



Typical Hold-Up Characteristic at 230 Vin

