



Characteristic Curves

TEL 8-2410WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




TEL 8-2411WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-2412WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-2413WI

Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-2415WI

Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-2422WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-2423WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-4810WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-4811WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-4812WI

Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-4813WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-4815WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-4822WI


Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic




Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise




Transient Response to Dynamic Load Change (25%)




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

TEL 8-4823WI

Efficiency versus Output Load




Efficiency versus Input Voltage




Typical Start-Up and Output Rise Characteristic



Derating Output Load versus Ambient Temperature



Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)

