

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Power supply for building-in

Name and address of the applicant

Traco Power Solutions Ltd.
Whitemill Industrial Estate Wexford, Whitemill Road,
Wexford Y35 YH66, Ireland

Name and address of the manufacturer

Traco Power Solutions Ltd.
Whitemill Industrial Estate Wexford, Whitemill Road,
Wexford Y35 YH66, Ireland

Name and address of the factory

Traco Power Solutions Ltd.
Whitemill Industrial Estate Wexford, Whitemill Road,
Wexford Y35 YH66, Ireland*Note: When more than one factory, please report on page 2* Additional Information on page 2

Ratings and principal characteristics

See next page

Trademark / Brand (if any)

**TRACO
POWER**[®]

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

See next page

Additional information (if necessary may also be reported on page 2)

Unit also complies with EN 62368-1:2014 + A11:2017

A sample of the product was tested and found to be in conformity with

 Additional Information on page 2

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0571/21 (2021-09-24)

This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2021-09-24

Signature: Bojan Pečavar



Model / Type Ref.:

24 W models: TMW 24-105, TMW 24-112, TMW 24-124

36 W models: TMW 36-112; TMW 36-124

* Models can be additionally marked with "P", where "P" indicates pin version

** models can be additionally marked with "xxaaaaa", where "x" or "a" can be any alphanumeric character, blank or dash (not impact on safety)

Ratings and principal characteristics**24 W models:**

Input: 100-240 Vac; 50/60 Hz; 0,5-0,25 A

Output:

TMW 24-105: 5,1 Vdc; 4,0 A

TMW 24-112: 12 Vdc; 2,0 A

TMW 24-124: 24 Vdc; 1,0 A

36 W models:

Input: 100-240 Vac; 50/60 Hz; 0,7-0,4 A

Output:

TMW 36-112: 12 Vdc; 3,0 A

TMW 36-124: 24 Vdc; 1,5 A

Additional information (if necessary)

Date: 2021-09-24

Signature: Bojan Pečavar

