



Characteristic Curves

THN 15-1210


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




THN 15-1211


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-1212


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-1213


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-1215


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-1221


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-1222


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-1223


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-1225


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2410


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2411


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2412


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2413


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2415


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2421


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2422


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2423


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-2425


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4810


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4811


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4812


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4813


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4815


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4821


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4822


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4823


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

THN 15-4825


Efficiency versus Output Load




Efficiency versus Input Voltage




Derating Output Load versus Ambient Temperature




Power Dissipation versus Output Load




Typical Output Ripple and Noise



Transient Response to Dynamic Load Change (25%)




Typical Start-Up and Output Rise Characteristic




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Derating Temperature versus Ambient Temperature (with Heat-Sink)


THN 15-1210




THN 15-1211




THN 15-1212




THN 15-1213




THN 15-1215




THN 15-1221



THN 15-1222




THN15-1223




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Derating Temperature versus Ambient Temperature (with Heat-Sink)


THN15-1225




THN15-2410




THN15-2411




THN15-2412




THN15-2413




THN15-2415



THN15-2421




THN15-2422




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Derating Temperature versus Ambient Temperature (with Heat-Sink)


THN15-2423




THN15-2425




THN15-4810




THN15-4811




THN15-4812




THN15-4813



THN15-4815




THN15-4821




All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Derating Temperature versus Ambient Temperature (with Heat-Sink)

THN15-4822



THN15-4823



THN15-4825

