



Ref. Certif. No.

DK-101095-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product

Switching Power Supply

Name and address of the applicant

TRACO ELECTRONIC AG
Sihlbruggstrasse 111 CH-6340 Baar, SWITZERLAND

Name and address of the manufacturer

TRACO ELECTRONIC AG
Sihlbruggstrasse 111 CH-6340 Baar, SWITZERLAND

Name and address of the factory

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)



Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

TPI 30-XYbzzzzzzzz
See Page 2

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to EN 62368-1:2014 / A11:2017
National Difference specified in the CB Test Report

☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

2002091-CB issued on 2020-07-22

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd L 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

Date: 2020-08-10

Signature:

Jan-Erik Storgaard

For full legal entity names see www.ul.com/ncbnames



Ref. Certif. No.

DK-101095-UL

Model Details:

TPI 30-XYbzzzzzzzz (X can be 103, 105, 107, 109, 112, 112.1, 115, 115.1, 118, 124, 128, 136, 148 or 153; Y can be A, S, D; b can be -M, -J, -D, -A1, -MA1, -JA1, -DA1 or blank; z can be any alphanumeric or blank for marketing purpose only and no impact safety related critical components and constructions.)

Ratings:

Input:

Construction A:

100-240 VAC, 50/60 Hz, 0.8 A Max. (For Models b can be -M, -J, -D or blank)

Construction B:

100-240 VAC, 50/60 Hz, 0.8 A Max. or 120-370 VDC, 0.8 A Max. (For Models b can be -A1, -MA1, -JA1, -DA1)

Output: See test report for details

Additional information (if necessary)



UL (US), 333 Pfingsten Rd L 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP) Marunouchi Trust Tower Main Building 6F 1-8-3 Marunouchi Chiyoda-ku Tokyo 100-0005 JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/nclnames

Date: 2020-08-10

Signature:

Jan-Erik Storgaard